

COPPER WIRE CUT & STRIP TOOLS

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-54151736
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

WIRE CUT-AND-STRIP TOOLS - ST-100 SERIES

A revolutionary concept for easy and clean stripping of wires for wire wrapping, electronic and appliance applications. Biomechanically designed for maximum efficiency.

Easy to operate... place wire (up to 4) in stripping slot with ends extending beyond cutter blades... press tool and pull... wire is cut and stripped to proper "wire wrapping" length. The hardened steel cutting blades and sturdy construction of the tool ensure long life. Strip length easily adjustable for your application. Blades are made from specially tempered spring steel for clean, nick-free wire stripping.



ST-100-30

Part No.	Wire Size		Adjustable Strip-Off Length		Replacement Blade
	AWG	mm	Inches	mm	
ST-100	22-24	0.65-0.50	1 5/16" to 1 9/16"	33.33 to 39.68	OK-3907B
ST-100-26	26	0.40	1 15/16" to 1 11/16"	33.33 to 42.86	OK-3907-26B
ST-100-28	28	.32	7/8" to 1 1/8"	22.22 to 28.57	OK-3907-28B
ST-100-30	30	.25	7/8" to 1 1/8"	22.22 to 28.57	OK-3907-30B

ADJUSTABLE PRECISION WIRE STRIPPERS OK-3907 SERIES

The OK-3907 Series from OK Industries is the industry's leading cut-and-strip tool for copper interconnect applications. Installers and telecom technicians enjoy its rugged construction, comfortable rubber grips, and high-leverage handle design, which allows time savings through the simultaneous cutting of multiple wires. Blades are made from specially tempered spring steel for clean, nick-free wire stripping.

Part No.	Wire Size		Adjustable Strip-Off Length		Replacement Blade
	AWG	mm	Inches	mm	
OK-3907	22-24	0.65	1-1/2" to 1-3/4"	38.10 to 44.45	OK-3907B
OK-3907-26	26	0.40	1-1/2" to 1-3/4"	38.10 to 44.45	OK-3907-26B
OK-3907-30	30	0.25	7/8" to 1 1/8"	22.22 to 28.57	OK-3907-30B



OK-3907

ADJUSTABLE PRECISION WIRE STRIPPERS ST-500 & ST-550

The ST-500 and ST-550 Adjustable Precision Wire Strippers feature an adjustment dial that allows the operator to select one of six different settings. A calibrated wire stop can then be adjusted for the desired insulation strip length. In a single motion, the operator squeezes and pulls the tool. This action engages four specially hardened blades to cleanly cut the wire insulation while the pulling motion breaks the insulation / conductor bond.

- Adjustable to six wire gauges:
 ST-500 20 to 30 AWG
 ST-550 18 to 28 AWG
- Calibrated Wire Stop
- Single action squeeze-pull motion
- Clean, precise strip of any insulation type
- Shirt-pocket size and light-weight (<1oz.)

Part No.	ST-500	ST-550
Wire Gauge	20-30 AWG	18-28 AWG
Calibrated Strip Length	Adjustable to 2" (50.8mm)	Adjustable to 2" (50.8mm)
Insulation Type	Any	Any
Dimensions (L x H x Thickness)	3.9" x 1.6" x 0.6" (99mm x 42mm x 14mm)	3.9" x 1.6" x 0.6" (99mm x 42mm x 14mm)
Housing Material	ABS	ABS
Blade	Hardened Steel (RC 58)	Hardened Steel (RC 58)



ST-500 & ST-550