

12~15W AC-DC Single Output Desktop P15A Ttpe

- 3 pole AC inlet IEC320-C14
- Full output 3~48V safety approval
- Short circuit protection
- Over load/ temp. Protection
- LED indicate for power on
- 100% full load burn-in test
- Fully enclosed plastic case
- DC output plug option
- Approvals: UL/CUL/ TUV/ CB/ CE
- Low cost/ OEM brand acceptable
- 1 year warranty

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-54151736
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)



AC input range	90~264VAC/ 0.5A
Inrush current	cold start, <30A peak @230VAC
Hold up time	8ms@ full load. 115VAC input
Over load protection	pulsing mode, auto recovery
Operating temperature	0~30 @100% load, 40 @60% load
Withstand voltage	I/P-O/P:3KVAC, I/P-FG: 1.5KVAC, 1min.
Safety standards	UL 1950, CSA 22.2, TUV EN60950
EMI standards	EN55022 class B, EN61000-3-2,3
EMS standards	EN61000-4-2,3,4,5,6,11, ENV50204
Length of output cable	180cm of SPT-1, 18AWG⊙ 2C
Standard plug of DC output	2.1N ₂ ⊙ 5.5N ₂ ⊙11mm. center"+

Stock No	Type No	Output	Tol.	R&N	Effi.	P.P.
13541	P15A-0P2J	3.3V, 0-2.18A	5%	50mV	55%	29
13542	P15A-1P2J	5V, 0-2.40A	5%	50mV	65%	29
13543	P15A-1-1P2J	7.5V, 0-1.60A	5%	80mV	72%	29
13544	P15A-2P2J	9V, 0-1.66A	5%	80mV	74%	29
13545	P15A-3P2J	12V, 0-1.25A	3%	80mV	75%	29
13546	P15A-4P2J	15V, 0-1.00A	3%	100mV	76%	29
13547	P15A-5P2J	18V, 0-0.83A	3%	100mV	78%	29
13548	P15A-6P2J	24V, 0-0.62A	3%	180mV	80%	29
13549	P15A-8P2J	48V, 0-0.31A	2%	300mV	80%	29