

勝 特 力 材 料 886-3-5753170 胜特力电子(上海) 86-21-54151736 胜特力电子(深圳) 86-755-83298787 Http://www.100y.com.tw


PE6V4.5



Dimensions







WWW.100Y.COM.TW **Rechargeable Sealed Lead Acid Battery**

Specifications

| 1 | Nominal Voltage | 6V 0.05C (0.225A to 5.25V) 4.50 AHr 0.1C (0.45A to 5.25V) 4.05 AHr 0.2C (0.90A to 5.10V) 3.51 AHr 1C (4.50A to 4.50V) 2.34 AHr | | | |
|----|--|--|--|--|--|
| 2 | Nominal Capacity | | | | |
| 3 | Weight (Approx.) | 1.96 lbs. (0.89 kg) | | | |
| 10 | Internal 60 milliohms Resistance of fully charged battery | | | | |
| 5 | Energy Density (0.05C) | 1.32 Watt-hours/cubic inch (80.5 Watt-hours/火) | | | |
| 6 | Specific Energy (0.05C) | | | | |
| 7 | Maximum Discharge Current with standard terminals | arge ent with ard | | | |
| 8 | Maximum Short 67.5 amperes Duration Discharge Current (less than 5 sec.) | | | | |
| 9 | Vibration Test | (2000 cycles/minute, 0.10 inchexcursion, 2 hours) No loss in capacity or performance | | | |
| | Charge Retention (shelf life) | % of nominal capacity at 77°F (25°C) 1 month 97% 3 months 91% 6 months 85% | | | |
| 1 | Operating Temperature Range | Charge 32°F (0°C) to 104°F (40°C) | | | |

WWW.100Y.COM.TW WWW.100Y.COM.TW 特力材料886-3-5753170 胜特力电子(上海) 86-21-54151736 胜特力电子(深圳) 86-755-83298787 WWW.100Y.CO! Http://www. 100y. com. tw

WWW.100Y.CO

| 12 | Case Material | Synthetic resin (ABS) |
|----|----------------------|-----------------------|
| 13 | Standard Terminal | VF100Y.COM.TW |

CHARGING METHODS

CYCLIC USE:

Maximum Initial Charge Current: 1.125A

Charging Voltage: 7.2V-7.35V


Charge should be switched to float mode or disconnected when current drops to 70mA

STANDBY USE:


Maximum Initial Charge Current: 1.125A

WWW.100Y.COM.T

Charge Voltage: 6.75V-6.9V




WWW.100Y.CC



V.100Y.COM.TW 勝 特 力 材 料 886-3-5753170 胜特力电子(上海) 86-21-54151736 胜特力电子(深圳) 86-755-83298787 Http://www. 100y. com. tw


W.100Y.COM.TW


WWW.100Y.COM.TW




WWW.100Y

WWW.100Y.COM.T







WWW.100Y.COM.

WWW.100

WWW.100Y.COM.TW 勝 特 力 材 料 886-3-5753170 胜特力电子(上海) 86-21-54151736 胜特力电子(深圳) 86-755-83298787 WWW.100Y.COM.TW Http://www. 100y. com. tw WWW.100Y.COM.TW

W.100Y.COM.TW