



## Indicator

## PPC Series

### Main Features

- LCD Display
- Counting by sample or Unit weight setting
- Auto Calibration
- Auto Zero Tracking
- Quantity Checking
- Power Saving Facility
- Build in rechargeable battery
- Accumulation Memories
- Charging indicator
- Overload Protection

### Options

- Backlit
- RS232 Interface

### Specifications

Model	SRC-L1.2	SRC-L3	SRC-L6	SRC-L12	SRC-L30
Capacity	1.2Kg	3Kg	6Kg	12Kg	30 Kg
Readability	0.2g	0.5g	1g	2g	5g
Resolution	0.04g	0.1g	0.2g	0.4g	1g
Pan Size	240x280 mm				
Power	AC Adaptor,9V/500Ma				
Weight	Approx. 6.8KG				
Environment	0°C ~ 40°C (32°F ~ 104°C) RH less than 85%				
Accessory	Manual, AC adaptor				

勝特力材料 886-3-5753170  
勝特力电子(上海) 86-21-54151736  
勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)



## Bench Scale

## BS Series

### Main Features

- Auto Zero Tracking
- Full Digital calibration(FDC)
- Full tare
- Kg/1b conversion
- Rechargeable battery
- Selectable counting sample(10.20.50.100)
- Best Viewing Angle for adjustable head
- 6digits large LCD numerals, 1 inch/25mm.
- Stainless steel platform
- Splash proof Construction
- Low battery warning
- Overload Protection

### Specifications

Model	BS-30	BS-60	BS-150	BS-60(OIML TYPE)	BS-150(OIML TYPE)
Capacity	30Kg	60Kg	150Kg	60Kg	150 Kg
Division	5g	10g	20g	20g	50g
Platform DIM.	320X420mm				
Operation Temperature	-10oC--40oC				
Power Supply	AC Adaptor, 9V/500 mA				
Dimension	320W x 420D x 650H (mm)				
Net Weight	11.5Kg				

勝特力材料 886-3-5753170  
 勝特力电子(上海) 86-21-54151736  
 勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)