

ALUMINUM COATED TIPS

R

LONG LIFE TIPS

SERIES

goot genuine replacement long life tips are iron plated then aluminum coated for superior durability.

MODEL	Available Tip Shape	Dia./ømm	Length/mm	Applicable soldering irons
RB-475B*1	B	4	75	KS/KX-20R,25R,30R,40R,60R,KYP-60,70
R-48	A, B, BC, C, D, SB, SC	4	75	CA-30R, CA-40R KS-20R, KS-30R, KS-40R KX-20R, KX-25R, KX-30R, KX-40R
R-6	B, BC, C, D, SB*2, SC*2	6	80	KS-60R, KX-60R
RB-680B*1	B	6	80	KS-60R, KX-60R
RD-67	B, BC, C*2, D*2	6-7	85	KS-80R, KX-80R
RD-68	B, BC, C*2, D*2	6-8	90	KS-100R, KX-100R

*1 BLACK TIP


Tips marked with a *2 may require a lead time before shipping. Please contact your nearest **goot** distributor for lead time confirmation.

REPLACEMENT TIP SHAPES

A TYPE



B TYPE



BC TYPE



C TYPE



D TYPE



SB TYPE



SC TYPE



TYPE		R-48	R-6	RD-67	RD-68						
A		a	0.5	-	-						
		b	9	-	-						
		c	ø4	-	-						
B		a	R0.5	R0.8	R0.8						
		b	9	12	12	20					
		c	7	10	10	17					
BC		a	1.2	2	2	2.5					
		b	9	12	15	20					
		c	45°	45°	45°	45°					
C		a	ø4	ø6	ø7	ø8					
		b	7	10	10	12					
		c	45°	45°	45°	45°					
D		a	1	1.2	1.3	1.5					
		b	3	4	4	4					
		c	13	25	28	30					
SB		a	R0.3	R0.3	-	-					
		b	14	18	-	-					
		c	ø2	ø3	-	-					
SC		a	ø2	ø3	-	-					
		b	14	18	-	-					
		c	45°	45°	-	-					

NICKEL PLATED TIPS

MODEL	Replacement Tip Shape	Dia./ømm	Length/mm	Applicable soldering irons
T-48	B	4	75	KX-20, KX-25, KX-30, KX-40
T-6	B	6	85	KX-60
TD-67	B	6-7	85	KX-80
TD-68	B	6-8	90	KX-100
T-13	A	13	120	HP-150
T-16	A	16	120	HP-200
T-19	A	19	140	HP-300

T

COPPER TIPS

SERIES

TYPE		T-48	T-6	TD-67	TD-68	T-13	T-16	T-19			
A		a	-	-	-	2	3	3			
		b	-	-	-	20	25	30			
		c	-	-	-	ø13	ø16	ø19			
B		a	R0.5	R0.5	R0.6	R0.6	-	-			
		b	10	15	15	17	-	-			
		c	-	-	-	-	-	-			

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-54151736
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)