

## Zelio relay range



### Main

Range of product	Zelio Relay
Product or component type	Socket
Contact terminal arrangement	Mixed
Product compatibility	Plug-in relay RXM (2 C/O)
Device short name	RXZ
Sale per indivisible quantity	10

### Complementary

[Ith] conventional free air thermal current	7 A
[Ue] rated operational voltage	250 V
Tightening torque	<= 0.8 N.m (M3 screw(s))
Fixing mode	Clip-on 35 mm symmetrical DIN rail By screw panel
Marking	CE
Width	22.5 mm
Product weight	0.034 kg

### Environment

Connections - terminals	Screw clamp terminals, solid cable without cable end 2 x 0.2...2 x 1.5 mm <sup>2</sup> /AWG 24...AWG 16 Screw clamp terminals, solid cable without cable end 1 x 0.2...1 x 2.5 mm <sup>2</sup> /AWG 24...AWG 14 Screw clamp terminals, flexible cable with cable end 2 x 0.5...2 x 1.5 mm <sup>2</sup> /AWG 20...AWG 16 Screw clamp terminals, flexible cable with cable end 1 x 0.2...1 x 2.5 mm <sup>2</sup> /AWG 24...AWG 14
Standards	IEC 61984
Ambient air temperature for storage	-55...85 °C
Ambient air temperature for operation	-40...55 °C
IP degree of protection	IP20 conforming to EN/IEC 60529
Dielectric strength	2500 V

Dimensions

