Pro Series SCSI II Cable - 10'

The Micro DB50 Male to

Centronics 50 Male Pro Series SCSI II (fast SCSI) Cable is used to interface two SCSI II devices, like a scanner and a CD-ROM, wherein one has a Micro DB50 female port and the other has a Centronics 50 female port. PRODUCT FEATURES: Rated for SCSI II applications; Double shielded (foil and braid) to meet SCSI specifications and ensure compliance with FCC requirements reducing EMI/RFI interference; Low-dapacitance impedance matched 28 AWG stranded tinned copper are individually insulated in polypropylene; 25 tightly woven conductor pairs ensure that each data line is paired with a ground line to minimize interference ensuring error-free data transmissions; Gold plated copper contacts for a clean, clear transmission; PVC premold encapsulates individual conductors to eliminate stress; Flextec PVC rubberized cable acket is extremely flexible for use in tight areas; Aluminum undermold shield helps meet FCC requirements; Ground indents provide excellent conductivity and retention with mating connector.



勝 特 力 材 料 886-3-5753170 胜特力电子(上海) 86-21-54151736 胜特力电子(深圳) 86-755-83298787 Http://www.100y.com.tw



Detailed Specifications

Manufacturer	W. JONY.CO. TW	Belkin
		WWW.100X.COM. TW WWW.100
Technical Information	Cable Type	SCSI external cable
	Cable Length	0.35M
	Total Connectors	2 N. 100 Y. 100 Y. 1
	Connector	1 x 50 pin HD D-Sub (HD-50) - male 1 x 50 pin Centronics - male
	Cable Grade/Rating/Specifics	28 AWG stranded tinned coppers
	Platform Support	PC Mac
	Conductor	Gold plated copper
	Jacket	Flextec PVC
Color		Beige
Physical Characterisitics	Dimensions	Shipping: (H x D)
	Weight	Shipping:
Warranty	WW.	Lifetime warranty