

# VOLT SLIDER(VARIABLE AUTOTRANSFORMER)

# VOLT SLIDER

## S3P-240 Series Three Phase 0-240V Output

| Specification/Model |                         | S3P-240<br>-2-S   | S3P-240<br>-3-S | S3P-240<br>-5-S | S3P-240<br>-10-S | S3P-240<br>-15-S | S3P-240<br>-20-S | S3P-240<br>-30-S |  |
|---------------------|-------------------------|---|-----------------|-----------------|------------------|------------------|------------------|------------------|--|
| Number of phase     |                         | 3 phase 3 wire  |                 | 3 phase 4 wire  |                  |                  |                  |                  |  |
| Output              | Voltage                 | 0-240V  |                 |                 |                  |                  |                  |                  |  |
|                     | Resolution(V)           | 0.5   | 0.6             | 0.7             | 0.9              | 1.1              | 1.1              | 1.3              |  |
|                     | Voltage Flucuation rate | within5%  |                 |                 |                  |                  |                  |                  |  |
|                     | Max Current(A)          | 2   | 3               | 5               | 10               | 15               | 20               | 30               |  |
|                     | Rated time              | 4hours  |                 |                 |                  |                  |                  |                  |  |
| Input               | Voltage                 | Please select from follow the voltage (200/220/230/240V etc.) |                 |                 |                  |                  |                  |                  |  |
|                     | Frequency               | 50/60Hz   |                 |                 |                  |                  |                  |                  |  |
| Standard            | Ambient Temperature     | 0-40C   |                 |                 |                  |                  |                  |                  |  |
|                     | Humidity                | 35-85%RH  |                 |                 |                  |                  |                  |                  |  |
|                     | Temperature rise        | Coil90C Core85C   |                 |                 |                  |                  |                  |                  |  |
|                     | Cooling                 | Self Cooling  |                 |                 |                  |                  |                  |                  |  |
|                     | Calorific Value(Kcal/h) | 29  | 44              | 74              | 149              | 224              | 298              | 449              |  |
| Figure              | Dimensions A(mm)        | 165   | 165             | 165             | 197              | 197              | 260              | 298              |  |
|                     | B(mm)                   | 145   | 145             | 145             | 175              | 175              | 235              | 275              |  |
|                     | C(mm)                   | 305   | 385             | 385             | 449              | 449              | 560              | 568              |  |
|                     | Weight (Kg)             | 9.5   | 12.5            | 13.5            | 21.5             | 25.5             | 40.0             | 55.0             |  |
|                     | Terminal Size           | M6  |                 |                 |                  |                  |                  |                  |  |
|                     | Figure                  | 7   |                 |                 |                  |                  |                  |                  |  |




Figure 7

**勝特力材料 886-3-5753170**  
**勝特力电子(上海) 86-21-54151736**  
**勝特力电子(深圳) 86-755-83298787**  
[Http://www.100y.com.tw](http://www.100y.com.tw)