

SOLDER FOR SPECIAL USE

SD-40 Series

SD-46

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-54151736
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)



Product Number	Description	M.P. /°C	Dia. / φ mm	Sn / %	Length / m
SD-40-06	RMA Solder	190	0.6	60	Approx. 5.7
SD-40-08	RMA Solder	190	0.8	60	Approx. 5
SD-40-10	RMA Solder	190	1.0	60	Approx. 4.3

Product Number	Description	M.P. /°C	Dia. / φ mm	Sn / %	Length / m
SD-41	Ag solder	211	0.8	60	Approx. 5
SD-42	Cu solder	257	0.8	60	Approx. 5
SD-45	Eutectic solder	184	0.8	63	Approx. 5
SD-46	Cream solder for stainless steel	184	—	63	Approx.10 (g)
SD-47	Pb (Lead) free solder (An,Ag,Cu,Bi)	215	1.0	95.7	Approx. 4.3
SD-48	Pb (Lead) free solder (Sn,Ag,Cu)	219	1.0	95.75	Approx. 4.3

Product Number	Description	M.P. /°C	Dia. / φ mm	Sn / %	Length / m
SD-215	Electronic use solder	215	1.2	50	Approx. 2.2

SD-47 is lead free solder that is the closest in characteristic to eutectic solder.

SD-48 has a higher melting point than eutectic solder however the crack occurrence rate is low while the anti-creep is especially high. *Anti-heat and crack resistant quality.