

20 MHz/10MHz/7MHz/4MHz DDS FUNCTION GENERATOR



NEW

SFG-2100 Series (20/10/7/4 MHz)



NEW

SFG-2000 Series (20/10/7/4 MHz)



FEATURES

- * DDS Technology and FPGA Chip Design
- * Frequency Range: 0.1Hz~4/7/10/20 MHz
- * High Frequency Accuracy : ± 20 ppm
- * High Frequency Stability : ± 20 ppm
- * Frequency Resolution : 100mHz
- * Low Distortion Sine Wave : -55dBc, 0.1Hz ~ 200kHz
- * Front Panel Setting Save/Recall with 10 Groups of Setting Memories
- * Built-in 9 Digits, 150MHz/High Resolution Counter (SFG-2100 Series Only)
- * INT/EXT AM/FM Modulation (SFG-2100 Series Only)
- * LIN/LOG Sweep Mode (SFG-2100 Series Only)

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-54151736
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

Based on Direct Digital Synthesized (DDS) technology and unique FPGA design, SFG-2000/2100 Series Function Generators are built with exceptionally high performance far exceeding that of any conventional function generators, at a very competitive price. Stable output frequency, low distortion, and fine frequency resolution are the most remarkable characteristics of this product series.

SFG-2000/2100 Series include four members in each family at 4MHz, 7MHz, 10MHz and 20MHz bandwidth, respectively. SFG-2100 Series has additional functions of Sweep, AM/FM modulation, and External Counter. As a result of the ± 20 ppm stability level and output waveform accuracy, SFG-2000/2100 Series well fits a wide variety of applications, such as signal generator for experiment labs, reference signal for PLL (Phase Locked Loop), and calibration and adjustment source for electronic devices.

SPECIFICATIONS		SFG-2000 Series				SFG-2100 Series			
MAIN		SFG-2004	SFG-2007	SFG-2010	SFG-2020	SFG-2104	SFG-2107	SFG-2110	SFG-2120
Frequency		0.1Hz~4MHz	0.1Hz~7MHz	0.1Hz~10MHz	1Hz~20MHz	0.1Hz~4MHz	0.1Hz~7MHz	0.1Hz~10MHz	1Hz~20MHz
Range(For Sine, Square)		0.1Hz~1MHz (1Hz ~ 1MHz for SFG-2020/2120)							
Range(For Triangle)		0.1Hz (1Hz for SFG-2020/2120)							
Resolution		± 20 ppm							
Stability		± 20 ppm							
Accuracy		± 5 ppm / year							
Aging		Sine, Square, Triangle							
Output Function		2mV ~ 10Vpp (into 50 Ω load)							
Amplitude Range		50 Ω $\pm 10\%$							
Impedance		-20dB ± 1 dBx2							
Attenuator		< -5V ~ +5V (into 50 Ω load)							
DC Offset		20% to 80%, 2Hz ~ 1MHz (Square wave only)							
Duty Control		1%							
Range Resolution		9 digits LED display							
Display									
SINE WAVE									
Harmonics Distortion		-55dBc, 0.1Hz~200kHz; -40dBc, 0.2MHz~4MHz; -30dBc, 4MHz~10MHz							
Flatness(Relative to 1kHz)		(Specification applied to both TTL/CMOS OFF and from MAX. to 1/10 level)							
Linearity		$\leq \pm 0.3$ dB, 0.1Hz~1MHz; $\leq \pm 0.5$ dB, 1MHz~4MHz; $\leq \pm 2$ dB, 4MHz~10MHz							
TRIANGLE WAVE									
Linearity		$\geq 98\%$, 0.1Hz~100kHz; $\geq 95\%$, 100kHz~1MHz							
SQUARE WAVE									
Symmetry		$\pm 1\%$ of period + 4ns, 0.1Hz~100kHz							
Rise or Fall Time		≤ 25 ns at maximum output. (into 50 Ω load)							
CMOS OUTPUT									
Level		4Vpp ± 1 Vpp~15Vpp ± 1 Vpp adjustable; Rise or Fall Time ≤ 120 ns							
TTL OUTPUT									
Level		≥ 3 Vpp; FanOut: 20 TTL load; Rise or Fall Time: ≤ 25 ns							
SWEEP OPERATION									
Rate						100:1 ratio max. and adjustable(*)			
Time						1Sec~30Sec adjustable(**)			
Mode		-				Lin./Log. switch selector			
AMPLITUDE MODULATION									
Depth & Modulation						0~100%; 400Hz(INT), DC~1MHz(EXT)			
Frequency						100Hz~5MHz(-3dB)			
Carrier BW						≤ 10 Vpp for 100% modulation			
EXT Modulation Sensitivity									
FREQUENCY MODULATION									
Deviation & Modulation						$\geq 0 \sim \pm 50$ kHz, center at 1MHz, 400Hz fixed(INT), 1kHz fixed(EXT)			
Frequency						≤ 10 Vpp for 10% modulation(center at 1kHz)			
EXT Modulation Sensitivity									
FREQUENCY COUNTER									
Range						5Hz~150MHz			
Accuracy						Time base accuracy ± 1 count			
Time base						± 20 ppm (23 $^{\circ}$ C $\pm 5^{\circ}$ C) after 30 minutes warm up			
Resolution						The maximum resolution is 100nHz for 1Hz and 0.1Hz for 100MHz			
Input Impedance						1M Ω /150pf			
Sensitivity						≤ 35 mVrms (5Hz~100MHz)			
						≤ 45 mVrms (100MHz~150MHz)			



SFG-2100 Series

Rear Panel



SPECIFICATIONS								
	SFG-2000 Series				SFG-2100 Series			
	SFG-2004	SFG-2007	SFG-2010	SFG-2020	SFG-2104	SFG-2107	SFG-2110	SFG-2120
STORE/RECALL FUNCTION	10 groups of Setting memories							
POWER SOURCE	AC115V±10%, AC230V+10%/-15%, 50/60Hz							
DIMENSION & WEIGHT	266(W)x107(H)x293(D) mm; Approx. 3.1kg				266(W)x107(H)x293(D) mm; Approx. 3.2kg			

ORDERING INFORMATION

- SFG-2004 4MHz DDS Function Generator
- SFG-2007 7MHz DDS Function Generator
- SFG-2010 10MHz DDS Function Generator
- SFG-2020 20MHz DDS Function Generator
- SFG-2104 4MHz DDS Function Generator with Counter, Sweep & AM, FM Modulation
- SFG-2107 7MHz DDS Function Generator with Counter, Sweep & AM, FM Modulation
- SFG-2110 10MHz DDS Function Generator with Counter, Sweep & AM, FM Modulation
- SFG-2120 20MHz DDS Function Generator with Counter, Sweep & AM, FM Modulation

ACCESSORIES:

- User manual x 1, Power Cord x 1
- GTL-101 x1 (SFG-2000 Series)
- GTL-101 x2 (SFG-2100 Series)

Note : 1.(*) In order to get maximum sweep span, the sweep time needs to be tuned on when adjust sweep span.
 2.(**) When the sweep time is too long, the stop frequency will reach and stay at the maximum frequency of instrument until the end of the sweep cycle.

SELECTION GUIDE								
FREQUENCY RANGE	4MHz		7MHz		10MHz		20MHz	
MODEL	SFG-2004	SFG-2104	SFG-2007	SFG-2107	SFG-2010	SFG-2110	SFG-2020	SFG-2120
DUTY	✓	✓	✓	✓	✓	✓	✓	✓
TTL/CMOS	✓	✓	✓	✓	✓	✓	✓	✓
DC OFFSET	✓	✓	✓	✓	✓	✓	✓	✓
LIN/LOG SWEEP		✓		✓		✓		✓
AM/FM MODULATION		✓		✓		✓		✓
EXT COUNTER		✓		✓		✓		✓

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-54151736
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)