

# MODEL TL-5104

International size reference: AA, ER14505



勝特力材料 886-3-5753170  
 勝特力电子(上海) 86-21-54151736  
 勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)

## TADIRAN LITHIUM BATTERIES

### TECHNICAL DATA



(Typical values @+25°C for batteries stored for one year or less)

■ Nominal capacity @ 2 mA, to 2V	2.1 Ah
■ Rated voltage	3.6 V
■ Weight	17.6g (0.62 oz)
■ Volume	8 cc
■ Operating temperature range	-55°C to +85°C
■ U.L. Component Recognition, MH 12193	



### AVAILABLE TERMINATIONS

SUFFIX- /S STANDARD	15-5104-21000
SUFFIX- /T SOLDER TABS	15-5104-31000
SUFFIX- /P AXIAL PINS	15-5104-41000
SUFFIX- /PT2 RADIAL PINS	15-5104-36000
SUFFIX- /TP POLARIZED TABS	15-5104-52000
SUFFIX- /PT POLARIZED TABS	15-5104-53000



## MEMORY BACKUP

Note: Any presentations in this data sheet concerning performance are for information purpose only and are not construed as warranties either expressed or implied, of future performance. Rev. B 04/03