

MODEL TL-5155

International size reference: 2/3AA, ER14335



勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-54151736
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

TADIRAN LITHIUM BATTERIES

TECHNICAL DATA



(Typical values @+25°C for batteries stored for one year or less)

■ Nominal capacity @ 0.5 mA, to 2V	1.45 Ah
■ Rated voltage	3.6 V
■ Weight	12.4g (0.437 oz)
■ Volume	5.7 cc
■ Operating temperature range	-55°C to +85°C
■ U.L. Component Recognition, MH 12193	



AVAILABLE TERMINATIONS

SUFFIX- /S STANDARD	15-5155-21000
SUFFIX- /T SOLDER TABS	15-5155-31000
SUFFIX- /P AXIAL PINS	15-5155-41000
SUFFIX- /PT2 RADIAL PINS	15-5155-36000
SUFFIX- /TP POLARIZED TABS	15-5155-52000
SUFFIX- /PT POLARIZED TABS	15-5155-53000



MEMORY BACKUP

Note: Any presentations in this data sheet concerning performance are for information purpose only and are not construed as warranties either expressed or implied, of future performance. Rev. B 04/03