

勝特力材料 886-3-5753170  
勝特力电子(上海) 86-21-54151736  
勝特力电子(深圳) 86-755-83298787  
Http://www.100y.com.tw



**TECHSPRAY™**

Product Information

# Zero Charge® Static Dissipative Floor Coating

Dissipative Floor Coating

1720

## Introduction

---

This product is a high gloss floor finish designed for use in electronic production areas, computer rooms and other static sensitive areas. Contains a non-migratory, static dissipative polymer, which will maintain a constant surface resistivity of  $10^6$ - $10^8$  ohms throughout the humidity spectrum.

### Features / Benefits

- Zinc Free
- High Gloss
- Slip Resistant
- Static Dissipation Even Works in Low Humidity

## Chemical Components

---

Tributoxyethyl Phosphate.....	(78-51-3)	<1%
Diethylene Glycol Monomethyl Ether.....	(111-77-3)	3-4%
Dipropylene Glycol Methyl Ether.....	(34590-94-8)	<1%
Octylphenoxypolyethoxyethanol.....	(9036-19-5)	<<1%
Nonylphenoxypolyethoxyethanol.....	(68412-54-4)	<<1%
Ammonium Hydroxide.....	(1336-21-6)	.1%
Dibutyl Phthalate.....	(84-74-2)	.89%
Acrylic Copolymer.....	(25987-66-0)	10-15%
NJ trd. sec.#00850201001-5391P		<5%
Perfluoroalkyl Phosphates		<<1%
Deionized Water.....	(7732-18-5)	75-85%
Polyethylene Polymer		<3%

## Environmental Policy

---

Techspray® is committed to developing products to ensure a safer and cleaner environment. We will continue to meet and sustain the regulations of all federal, state and local government agencies.

## Packaging and Availability

---

Zero Charge® Static Dissipative Floor Coating is available in the following sizes:

1720-G	1 Gallon in Plastic
1720-5G	5 Gallons in Plastic
1720-54G	54 Gallons in Plastic

勝特力材料 886-3-5753170  
勝特力电子(上海) 86-21-54151736  
勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)

## Resources

---

Techspray® products are supported by a global sales, technical and customer services resources.

For additional technical information on this product or other Techspray® products in the United States, call the technical sales department at 800-858-4043, email [tsales@techspray.com](mailto:tsales@techspray.com) or visit our web site at: [www.techspray.com](http://www.techspray.com).

North America  
Tech Spray L.P.  
P.O. Box 949  
Amarillo, TX 79105  
800-858-4043  
email: [tsales@techspray.com](mailto:tsales@techspray.com)

Europe  
Techspray International  
UNIT 4, 44/46 Bunyan Road, Kempston  
Bedford MK42 8HL United Kingdom  
+44 (0) 1234 855443  
email: [tseurope@techspray.com](mailto:tseurope@techspray.com)

Countries Outside US  
Call to locate a distributor  
in your country.

Important Notice to Purchaser/User: The information in this publication is based on tests that we believe are reliable. The results may vary due to differences in tests type and conditions. We recommend that each user evaluate the product to determine its suitability for the intended application. Conditions of use are outside our control and vary widely. Techspray's only obligation and your only solution is replacement of product that is shown to be defective when you receive it. In no case will Techspray® be liable for any special, incidental, or consequential damages based on breach of warranty, negligence or any other theory.



Tech Spray, L.P.  
P.O. Box 949  
Amarillo, TX 79105  
[www.techspray.com](http://www.techspray.com)

[English MSDS](#)  
[French MSDS](#)  
[German MSDS](#)  
[Italian MSDS](#)  
[Spanish MSDS](#)

