



Test Leads & Accessories

KAG-2




- The 2mm plug is machined from brass with movable multilam contact cage spring
- Contact surface : Gold-plated
- Rated current : 50V 10A
- Color : Black, Red, Yellow, Blue, White, Green

KBG-2




- The 2mm plug is machined from brass with movable multilam contact cage spring
- Contact surface : Gold-plated
- Rated current : 50V 10A
- Color : Black, Red, Yellow, Blue, White, Green

KHG-4 / KHN-4




- The 4mm stackable safety plug is machined from brass with movable multilam contact cage spring
- Contact surface : Gold/Nickel-plated
- Rated current : 50V 19A
- Color : Black, Red, Yellow, Blue, White, Green

KAG-4 / KAN-4




- The 4mm stackable plug is machined from brass with movable multilam contact cage spring
- Contact surface : Gold/Nickel-plated
- Rated current : 50V 19A
- Color : Black, Red, Yellow, Blue, White, Green

KBG-4 / KBN-4




- The 4mm plug is machined from brass with movable multilam contact cage spring
- Contact surface : Gold/Nickel-plated
- Rated current : 50V 19A
- Color : Black, Red, Yellow, Blue, White, Green

KDN-42 / KDN-44




- Adaptors for interconnecting between 2mm and 4mm system
- 4mm plug to 2mm socket
- 4mm plug to 4mm socket
- Contact surface : Nickel-plated
- Rated : 50V 19A
- Color : Black, Red

KEG-4 / KEN-4




- A range of shrouded 4mm sockets offered for soldering or 6.4mm fast termination
- Panel mounting hole : 12 x 11mm
- Contact surface : Gold/Tin-plated
- Rated: 50V 19A
- Color : Black, Red, Yellow, Blue, White, Green

KFG-4 / KFN-4




- A range of shrouded 4mm sockets offered for soldering or 6.4mm fast termination
- Panel mounting hole : 12.4mm
- Contact surface : Gold/Tin-plated
- Rated: 50V 19A
- Color : Black, Red, Yellow, Blue, White, Green

Electronic Training Equipment & Breadboard / Accessories




KPG-2A




- A range of 2mm panel mounting socket accepts a wide range of 2mm plugs
- Panel mounting hole : 6 x 5mm
- Contact surface : Gold-plated
- Rated : 50V 10A
- Color : Black, Red, Yellow, Blue, White, Green

KPG-4A / KPN-4A




- A range of panel mounting 4mm sockets offered for soldering or 6.4mm fast termination
- Panel mounting hole : 8 x 7mm
- Contact surface : Gold/Tin-plated
- Rated : 50V 19A
- Color : Black, Red, Yellow, Blue, White, Green

KSN-40




- A range of 2mm socket designed for easy and quick assembly
- Panel mounting hole 6mm
- Contact surface : Nickel-plated
- Rated : 50V 10A
- Color : Black, Red, Yellow, Blue, White, Green

KSN-60




- A range of 4mm socket designed for easy and quick assembly
- Panel mounting hole 8mm
- Contact surface : Nickel-plated
- Rated : 50V 19A
- Color : Black, Red, Yellow, Blue, White, Green

KCG-210




- The 2mm connecting plug suitable for general interconnection on 2mm socket
- Contact surface : Gold-plated
- Rated : 50V 10A
- Spacing : 10mm
- Color : Black

KCN-419




- The 4mm connecting plug suitable for general interconnection on 4mm socket
- Contact surface : Nickel-plated
- Rated : 50V 19A
- Spacing : 19mm
- Color : Black

KCN-419A




- The safety 4mm connecting plug suitable for general interconnection on 4mm safety socket
- Contact surface : Nickel-plated
- Rated : 50V 19A
- Spacing : 19mm
- Color : Black

KCN-419B




- The safety 4mm connecting plug with two 4mm in-line safety socket suitable for general interconnection on 4mm safety socket
- Contact surface : Nickel-plated
- Rated : 50V 19A
- Spacing : 19mm
- Color : Black












Electronic Training Equipment & Breadboard / Accessories




<p>KWG-4 / KWN-4</p>  <ul style="list-style-type: none"> • 4mm stackable safety plug with cage springs • Contact surface : Gold/ Nickel-plated • Rated : 50V 19A • Length : 25.50.75.100cm 	<p>KLG-4 / KLN-4</p>  <ul style="list-style-type: none"> • 4mm stackable plug with cage springs • Contact surface : Gold/Nickel-plated • Rated : 50V 19A • Length : 25.50.75.100cm 	<p>KMG-4 / KMN-4</p>  <ul style="list-style-type: none"> • 4mm plug with cage springs • Contact surface : Gold/Nickel-plated • Rated : 50V 19A • Length : 25.50.75.100cm 	<p>KLG-2</p>  <ul style="list-style-type: none"> • 2mm stackable plug with cage springs • Contact surface : Gold-plated • Rated : 50V 10A • Length : 15.30.45.60cm
<p>Color: Black, Red, Yellow, Blue, White, Green</p>	<p>Color: Black, Red, Yellow, Blue, White, Green</p>	<p>Color: Black, Red, Yellow, Blue, White, Green</p>	<p>Color: Black, Red, Yellow, Blue, White, Green</p>
<p>KMG-2</p>  <ul style="list-style-type: none"> • 2mm plug with cage springs • Contact surface : Gold-plated • Rated : 50V 10A • Length : 15.30.45.60mm 	<p>KLG-0.5</p>  <ul style="list-style-type: none"> • 0.5mm plug is machined from phosphor bronze. • 2.5Φ Test-Ring in parallel • Contact surface : Gold-plated • Rated : 50V 10A • Length : 15.30.45.60cm 	<p>KLG-0.5-2</p>  <ul style="list-style-type: none"> • Adapter lead with 0.5mm plug and 2mm plug • Contact surface : Gold-plated • Rated : 50V 10A • Length : 15.30.45.60cm 	<p>KLG-2-4</p>  <ul style="list-style-type: none"> • Adapter lead with 2mm plug and 4mm plug • Contact surface : Gold-plated • Rated : 50V 10A • Length : 25.50.75.100cm
<p>Color: Black, Red, Yellow, Blue, White, Green</p>	<p>Color: Black, Red, Yellow, Blue, White, Green</p>	<p>Color: Black, Red, Yellow, Blue, White, Green</p>	<p>Color: Black, Red, Yellow, Blue, White, Green</p>
<p>CT-26</p>  <ul style="list-style-type: none"> • Ready assembled leads wire approx. 0.6M of 133/0.07mm extra flexible cable • Terminated at one end by a 2mm stackable plug and a 35mm long crocodile clip at the other 	<p>CT-41</p>  <ul style="list-style-type: none"> • Ready assembled leads wire approx. 1M of 301/0.07mm extra flexible cable • Terminated at one end by a 4mm stackable plug and a 35mm long crocodile clip at the other • Contact surface : Nickel-plated 	<p>CT-42</p>  <ul style="list-style-type: none"> • Ready assembled leads wire approx. 1M of 301/0.07mm extra flexible cable • Terminated at one end by a 4mm stackable safety plug and a 35mm long crocodile clip at the other • Contact surface : Nickel-plated 	<p>LF-51</p>  <ul style="list-style-type: none"> • Fully insulated leads with shrouded BNC plugs complete with moulded-on strain reliefs using RG-58 cable • Black PVC : shield. 50Ω impedance • Length : Overall length approx. 1M
<p>Color: Black, Red</p>	<p>Color: Black, Red</p>	<p>Color: Black, Red</p>	<p>Color: Black</p>

Electronic Training Equipment & Breadboard / Accessories



<p>LF-56</p>  <ul style="list-style-type: none"> Fully insulated BNC test leads whose impedance 50Ω. With RG-58 cable which is moulded to be 35mm long crocodile clips in red and black. Length : Overall length approx.1M 	<p>LF-61</p>  <ul style="list-style-type: none"> Fully insulated BNC test leads whose impedance 50Ω. With RG-58 cable which is moulded to be stackable 4mm plugs in red and black. Length : Overall length approx.1M 	<p>LF-101</p>  <ul style="list-style-type: none"> The oscilloscope probe body is integrated x1/x10 slide switch with trimming adjustment when in the x10 position. Bandwidth : DC to 60MHz ± 3db Max. Voltage : 600V DC Length : Overall length approx.1.2M 	<p>LF-210</p>  <ul style="list-style-type: none"> The oscilloscope probe body is integrated x1/x10 slide switch with trimming adjustment when in the x10 position. Bandwidth : DC to 100MHz ± 3db Max. voltage : 600V DC Length : Overall length approx.1.2M
<p>Color: Black</p>	<p>Color: Black</p>	<p>Color: Black</p>	<p>Color: Black</p>
<p>CC-35</p>  <ul style="list-style-type: none"> A set of crocodile clips with insulating vinyl cover Clips are 31mm long. Overall length with sleeve 38mm 	<p>CL-15</p>  <ul style="list-style-type: none"> A set of ten leads wire approx. 370mm long. Terminated at each end with a vinyl insulated crocodile clip 	<p>PC-40</p>  <ul style="list-style-type: none"> A miniature plunger action probes suited for making contact with components on high density PCBs. Overall length 40mm 	<p>PL-15</p>  <ul style="list-style-type: none"> A set of five leads wire approx. 370mm long. Terminated at each end with an insulated miniature probes
<p>Color: Red, Black, Yellow, Green, White</p>	<p>Color: Red, Black, Yellow, Green, White</p>	<p>Color: Red, Black, Yellow, Green, Blue</p>	<p>Color: Red, Black, Yellow, Green, Blue</p>
<p>PT-22</p>  <ul style="list-style-type: none"> A pair of multimeter test leads is well suited to meter with shrouded 4mm connector. The leads are CE approved. IEC-1010 compatible. Terminated at one end with a rigid probe and a fixed sheath or right angle with retractable shrouded 4mm plug at the other. Length : Overall length approx. 1M Rate : 1000V,10A 	<p>PT-23</p>  <ul style="list-style-type: none"> A set of fully insulated leads with probes and clips. Terminated at one end with a rigid probe including a crocodile clip and a fixed sheath or right angle with retractable shrouded 4mm plug at the other. Length : Overall length approx.1M Rate : 1000V,10A (clip excepted). 	<p>PT-24</p>  <ul style="list-style-type: none"> A set of fully insulated leads with probes and clips. Terminated at one end with a rigid probe including a crocodile clip and a fixed sheath or right angle with retractable shrouded 4mm plug at the other. Length : Overall length approx.1M Rate : 1000V,10A (clip excepted). 	
<p>Color: Black, Red</p>	<p>Color: Black, Red</p>	<p>Color: Black, Red</p>	

Electronic Training Equipment & Breadboard / Accessories



<p>KBL-2</p> <p>KBL-4</p> <ul style="list-style-type: none"> • Bezel to suit 2/4mm socket for identification purpose • Suited for KSG-2/ KSG-4 • Panel mounting hole : 4.2/6.2mm • Color : Black, Red, Yellow, Blue, White 	<p>KSG-2</p> <p>KSG-4</p> <ul style="list-style-type: none"> • 2/4 mm PCB mounting socket • Mounting hole 2.8/4.8mm • Contact surface : Gold-plated • Rated : 50V 10/19A
<p>KSG-30</p> <p>KSG-30A</p> <ul style="list-style-type: none"> • Uninsulated 2mm chassis mounting socket • Mounting hole 3.1mm • Contact surface : Gold-plated • Rated : 50V 10A <ul style="list-style-type: none"> • A range of 2mm socket designed for easy and quick assembly • Mounting hole 4.2mm • Contact surface : Gold-plated • Rated : 50V 10A 	<p>KSN-34</p> <p>KSN-56</p> <ul style="list-style-type: none"> • Uninsulated 2/4mm chassis mounting socket • Mounting hole 4/6mm • Contact surface : Nickel-plated • Rated : 50V 10/19A
	<p>KRN-41</p> <p>KRN-42</p> <ul style="list-style-type: none"> • A 4 mm Multilam plug with center hex-shape and threaded post or solder hole • Contact surface : Nickel-plated • Rated : 50V 19A

*Remarks : All of our plugs, adaptors and test leads could be sold per pack with hanging card. Please refer to our price list for detail description. Thanks!

ORDERING INFORMATION

