

MODEL TL-5151

International size reference: 1/2AA, ER14252



勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-54151736
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

TADIRAN LITHIUM BATTERIES

TECHNICAL DATA



(Typical values @+25°C for batteries stored for one year or less)

■ Nominal capacity @ 0.5 mA, to 2V	0.7 Ah
■ Rated voltage	3.6 V
■ Weight	9.2g (0.324 oz)
■ Volume	4.3 cc
■ Operating temperature range	-55°C to +85°C
■ U.L. Component Recognition, MH 12193	



AVAILABLE TERMINATIONS

SUFFIX- /S STANDARD	15-5151-21000
SUFFIX- /T SOLDER TABS	15-5151-31000
SUFFIX- /P AXIAL PINS	15-5151-41000
SUFFIX- /PT2 RADIAL PINS	15-5151-36000
SUFFIX- /TP POLARIZED TABS	15-5151-52000
SUFFIX- /PT POLARIZED TABS	15-5151-53000



MEMORY BACKUP

Note: Any presentations in this data sheet concerning performance are for information purpose only and are not construed as warranties either expressed or implied, of future performance.

Rev. B 03/03