

Special Meters


TM-102 Sound Level Meter

*** Auto Ranging**

is designed and built according to IEC 651 Type 2, ANSI S1.4 Type 2.



DISPLAY

- 3 1/2 digits LCD Digital display
- Resolution:0.1dB,Display update:0.5 sec.
- Low battery indication: Replace battery with LCD displays"  "

FEATURES

- Back light .
- Auto power off .
- Auto ranging .

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-54151736
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

SPECIFICATION

Microphone	1/2 inch Electret condenser microphone
Frequency range	31.5Hz~8KHz
Measuring level range	A weighting 30~130 dB (Auto Range)
	C weighting 35~130 dB (Auto Range)
Frequency weighting	A.C.
Time weighting	FAST,SLOW
Dynamic range	50dB
Accuracy	1.5dB

ACCESSORIES

- User's manual
- Carrying case
- 9V battery x 1pc

POWER SUPPLY

- Batter type :9V NEDA 1604 , IEC 6F22, JIS 006P x 1 pc.
- Battery life :About 30 hours.(with alkaline battery)

OPERATING CONDITIONS

- Operation temperature & humidity:5°C~40°C, below 80% RH.
- storage temperature & humidity:-10°C~60°C, below 70%RH.

Dimensions

- Size:200x 55 x38 mm(LxWxH)
- Weight:About 300g(including battery)