

勝特力材料 886-3-5753170
勝特力電子(上海) 86-21-54151736
勝特力電子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

- For electrical measurements on civil and industrial plant.

- **3 1/2 digits LCD with maximum reading 1999, Plus decimal point, unit symbol indication.**
- **Overload Indication: LCD will show “1” in the upper left position.**
- **Low Battery Indication: Replace battery as LCD display “ ”.**

- Auto Range
- Auto power off
- Function keys: Data Hold
- Test Ranges: DCV, ACV, ACA, Ω , Diode, Continuity
- The maximum conductor size is 30mm.

- **Sampling Rate: 2 times per second for digital display.**

- **Instruction manual**
- **Test leads**
- **1.5V Battery x 2pcs**

- **Battery type:** R03(AB)/SIZE AAA 1.5V/UM4 x 2pcs
- **Battery Life:** about 200 hours.

- **Operating Temperature & Humidity:** 5°C ~ 40°C, below 80%RH.
- **Storage Temperature & Humidity:** -10°C ~ 60°C, below 70%RH.

- **Size** : 195 x 64 x 30mm (LxWxH)
- **Weight**: about 240g. (including battery)

