

TM-181 : Hygro-Thermometer**Temperature/Humidity Meters****TM-181 Hygro-Thermo Meter****TENMARS****DISPLAY**

- 3 1/2 digits back light LCD with maximum reading 2000, plus decimal point, unit symbol indication.
- Sampling rate: 2.5 times per second.

FUNCTIONS

- Alternative measuring by °C or °F
- Temperature and Humidity alarm beep sound when temperature display reaches high/low limit.
- Auto power off.
- Real Time with Max Min Recording.
- Hold Function.
- REL (relative) Function.
- Suitable for electric engineering, freezing, air conditioning, food processing fields as well as surface temperature, metal, steel, electricity, chemical, ship building, synthetic resin process and metal heat process or other temperature control/management fields.

SPECIFICATIONS

- Temperature measure ranges: -40°C ~ 60.0°C (-40°F ~ 140°F)
- Humidity measure ranges: 1.0 ~ 99.0 RH.
- Resolution: 0.1°C/ 0.1°F (-40°C/°F ~ 99.9°C/°F); 0.1% RH.
- Accuracy: 0.5°C, 2.5% RH.

DIMENSION

- Size: 200 x 55 x 38mm (L x W x H)
- Weight: About 165g (including battery)

POWER SUPPLY

- Battery type: 9V NEDA 1604 IEC
- 6F22 JIS 006P x 1pc.
- Battery life: About 200 hours.

ACCESSORIES

- User's manual
- Carrying case
- 9V battery x 1pc

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-54151736
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)