

**TM-23E** Digital AC Clamp-on Meter are designed and built for use in an environment of pollution degree 2 according to IEC 1010-1 CAT II 1000V, IEC 1010-1 CAT III 600V and IEC1010-2-032 CAT III 600V.

勝特力材料 886-3-5753170  
勝特力电子(上海) 86-21-54151736  
勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)

## DISPLAY

- Display: 3 1/2 digits LCD with maximum reading 1999, plus decimal point, unit symbol indication.
- Overload Indication: LCD will show “1” in the upper left position.
- Low Battery Indication: Replace battery immediately when LCD displays “ ”.

## FUNCTIONS

- Auto range
- Function Key: Data hold
- Test Ranges: ACV, ACA, O, Continuity
- The maximum conductor size is 35mm.

## SAMPLING SPEED

- Sampling Rate: 2 times per second for digital display.

## ACCESSORIES

- Instruction manual
- Carrying case
- Test leads
- 1.5V Battery x 2 pcs

## POWER SUPPLY

- Battery type : 1.5V/UM3 1.5Vx2 NEDA 15F IEC R6 JIS UM-3
- Battery Life: about 200 hours.

## OPERATION CONDITION ?

- Operating Temperature & Humidity: 5 ~ 40 , below 80%RH.
- Storage Temperature & Humidity: -10 ~ 60 , below 70%RH.

## DIMENSION?

- Size : 218x75x43mm (LxWxH)
- Weight : about 335g (including battery)

