




勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-54151736
 勝特力电子(深圳) 86-755-83298787
 Http://www.100y.com.tw

TS4417


Surface Mount Series
 Tact Switch

ADD TO INQUIRY BASKET




unit:mm

CIRCUIT DIAGRAM



P.C.B LAYOUT



1. Rating : DC 12V, 50mA
2. Travel : 0.2±0.1m/m
3. Operating Force : 160 ±30gf
or 250 ±50gf
4. Contact Resistance : 50m Ω MAX
5. Life : 100,000 Cycles Min

| Model No. | Knob(L) |
|-----------|---------|
| TS4417 | 1.5mm |
| TS4417A | 4.3mm |

| ITEM | DESCRIPTION | Q'TY | MATERIALS | TREATMENT | REMARK |
|------|-------------|------|--------------------|------------|--------|
| 1 | BASE | 1 | NYLON 46 G30% | UL 94 | |
| 2 | COVER | 1 | SUS304-BA | | |
| 3 | STEM | 1 | NYLON 46 G30% | UL 94 | |
| 4 | TERMINAL | 1 | BRASS t=0.2 | Ag plating | |
| 5 | CONTACTOR | 1 | CS20R-BH t=0.05 | Ag plating | |