

# Technical Data Sheet

PRODUCT DESCRIPTION:	Ultralube Cleaning Solvent	DATE:	03/97
PRODUCT CODE:	ULS	PAGES:	1

## PRODUCT DESCRIPTION

Ultralube Cleaning Solvent is a fast-drying solvent specially formulated for the quick and efficient cleaning of electrical equipment. It replaces CFC solvents such as 113 trichloroethane due to rapid cleaning and fast evaporation rates. Ultralube is 100% Ozone Friendly. A full range of cleaning solvents are available from Electrolube. The range includes fast and slow drying solvents and water based products. Specialist flux cleaners are also available.

## PRODUCT USE

Electrical contacts, tape heads, PCBs, components in electronic and video equipment, computers, optical and precision instruments, cameras etc. Product contains **flammable solvent** so do not spray onto live electrical equipment or other sources of ignition. Immerse surface to be cleaned or spray onto surface to excess and allow to evaporate. A brush or foam tipped bud may be used to remove any stubborn deposits.

## FEATURES

- \* Non-CFC, non-halogenated cleaning solvent will not attack the Ozone Layer.
- \* Excellent removal of greases, oils, flux residues and acrylic conformal coatings from PCBs.
- \* Leaves a perfectly clean, dry surface - conventional solvents often leave greasy deposits which attract dust and dirt.
- \* Harmless to most plastics, rubbers, elastomers, and surface coatings.
- \* CO<sub>2</sub> propelled aerosol version available containing 20% more active cleaner.

## PROPERTIES

Specific Gravity @ 20°C:	0.79
Inhalation Toxicity:	300 ppm
Flash Point:	0°C
Residue on Evaporation:	<1ppm
Evaporation Rate:	16 (with ether as 1)

## PACKAGING

12ml Pen - Packed in 5's  
200ml Aerosol  
400ml Aerosol  
400ml Aerosol with Brush  
1 Litre Bulk  
5 Litre Bulk  
25 Litre Bulk

## ORDER CODE

ULS12P  
ULS200D  
ULS400D  
ULS400DB  
ULS01L  
ULS05L  
ULS25L

勝特力材料 886-3-5753170  
勝特力电子(上海) 86-21-54151736  
勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)

## Copyright Electrolube 1997

All information is given in good faith but without warranty. Properties are given as a guide only and should not be taken as a specification. Electrolube cannot be held responsible for the performance of its products within any application determined by the customer, who must satisfy themselves as to the suitability of the product.