

# CROSS REFERENCE

## BY MANUFACTURER / LAMP #

勝特力材料 886-3-5753170  
 勝特力电子(上海) 86-21-54151736  
 勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)

MANUFACTURER LAMP #	USHIO LAMP #	APPLICATION PROCESS	PAGE #
<b>KUHNAST (continued)</b>			
JGMH3000-0	MHL-3001	Diazo	59
JGMH3000-7	MHL-3007	Multi-Spectrum	60
JGMH3090-0	MHL-121HT	Diazo	51
JGMH3090-8	MHL-121HT	Diazo	51
JGMH4000-0	MHL-4001	Diazo	62
JGMH4000-7	MHL-4007	Multi-Spectrum	62
JGMH500-0S	MHL-12	Diazo	49
JGMH5000-7	MHL-5007	Multi-Spectrum	64
JGMH5010-8	MHL-5000/5	Photopolymer	64
JGMH550-0	MHL-12	Diazo	49
<b>MAC BETH</b>			
MX-07	UPX-42		68
MX-14	UPX-45		68
MX-15H	UPX-56		69
MX-28	UPX-47		69
MX-50H	UPX-50		69
MX-80H	UPX-80		69
<b>NUARC</b>			
CN-42, VE357	UPX-50		69
CU-71, VE409	UPX-80		69
FS90	MHL-4000/U1	Multi-Spectrum	61
GW114	MHL-1000/1	Photopolymer	56
	MHL-1000/2	Diazo	56
HE-15, VE-677	UPX-56		69
HT121	MHL-121HT	Diazo	51
HT28	MHL-2000/1	Diazo	58
HQ89	MHL-4000/U2	Photopolymer	61
KM5	MHL-121HT	Diazo	51
KT38	MHL-38KT	Diazo	51
KT98	MHL-38KT	Multi-Spectrum	51
LY33	MHL-33LY	Multi-Spectrum	51
MH153	MHL-153LY	Multi-Spectrum	52
VE366	FAD		29
VE377	DXX		29
VE479	FFM		28
VE598	EHP		28
VE66	SM-100T8/1SC		34
VE959	ENH		37
VE980	EYH		31

MANUFACTURER LAMP #	USHIO LAMP #	APPLICATION PROCESS	PAGE #
<b>OLEC</b>			
L1CP	EVA		32
L1KS	JCV120V-1000WC4		32
L1K3	BRH		30
L1250	MHL-170L	Diazo	52
L1250R	MHL-170LR	Diazo Matchprint	52
L1261	MHL-261L	Photopolymer	53
L1280	MHL-280L	Diazo	53
L1281	MHL-281L	Multi-Spectrum	53
L1282	MHL-282L	Multi-Spectrum	53
L6C2	FCB		28
<b>ORC</b>			
MXA-7000H	MHL-7000	Diazo	66
SMX-7000H	MHL-7007	Multi-Spectrum	66
<b>PHILIPS</b>			
HPA1000/20	MHL-1007	Multi-Spectrum	56
HPM12	MHL-12	Diazo	49
HPM13	MHL-13	Diazo	49
HPM15	MHL-15	Diazo	50
HPM16	MHL-16	Diazo	50
HPM17	MHL-17	Diazo	50
HPM19 (BT)	MHL-2000/3	Diazo	58
HPM20	MHL-3000/2	Diazo	59
HPM30	MHL-30	Diazo	50
TL8W54	F8T5/D		46
<b>SANDMAR</b>			
10431	MHL-1000/1	Photopolymer	56
L1250	MHL-170L	Diazo	52
L1250M	MHL-170LR	Diazo Matchprint	52
<b>STARNA</b>			
STR 530-0	MHL-12	Diazo	49
STR1000-0	MHL-1000	Diazo	55
STR1000-7	MHL-1007	Multi-Spectrum	56
STR1000-7S	MHL-1007S	Multi-Spectrum	56
STR2000-0	MHL-2000/3	Diazo	58
STR2000-8	MHL-2000/2	Photopolymer	58
STR2030-0	MHL-15	Diazo	50
STR2110-7S	MHL-2117S	Multi-Spectrum	59

MANUFACTURER LAMP #	USHIO LAMP #	APPLICATION PROCESS	PAGE #
<b>STARNA (continued)</b>			
STR2120-0	MHL-13	Diazo	49
STR3000-0	MHL-3001	Diazo	59
STR3000-0S	MHL-3001S	Diazo	60
STR3000-7	MHL-3007	Multi-Spectrum	60
STR3000-7S	MHL-3007S	Multi-Spectrum	60
STR4000-0	MHL-4001	Diazo	62
STR4000-7	MHL-4007	Multi-Spectrum	62
STR4010-0	MHL-4010	Diazo	62
STR5000-0	MHL-5000	Diazo	63
STR5000-0S	MHL-5000S	Diazo	63
STR5000-7	MHL-5007	Multi-Spectrum	64
STR5000-7S	MHL-5007S	Multi-Spectrum	64
STR5010-0	MHL-5000/4	Diazo	63
STR5010-8	MHL-5000/5	Photopolymer	64
STR5020-0	MHL-5020	Diazo	65
STR5020-0S	MHL-5020S	Diazo	65
STR5020-7	MHL-5027	Multi-Spectrum	65
STR5020-7S	MHL-5027S	Multi-Spectrum	66
STR5060-7	MHL-5027	Multi-Spectrum	66
STR5090-0	MHL-17	Diazo	50
<b>SYLVANIA</b>			
H2000T8/J	MHL-2000/2	Photopolymer	58
H5000T8/V	MHL-5000/5	Photopolymer	64
M001	MHL-12	Diazo	49
M001.J			
M001.Q			
M012	MHL-2000/3	Diazo	58
M017	MHL-4001	Diazo	62
M019	MHL-2000/3	Diazo	58
M022	MHL-4010	Diazo	62
M023	MHL-4001	Diazo	62
M024.1	MHL-1000	Diazo	55
M024.2	MHL-1000S	Diazo	55
M025	MHL-3001	Diazo	59
M025.2	MHL-3001S	Diazo	60
M026	MHL-5000	Diazo	63
M026.2	MHL-5000S	Diazo	63
M033	MHL-4007	Multi-Spectrum	62
M038	MHL-15	Diazo	50
M044	MHL-2000/3	Diazo	58

MANUFACTURER LAMP #	USHIO LAMP #	APPLICATION PROCESS	PAGE #
<b>SYLVANIA</b>			
M044.1	MHL-2000/3	Diazo	58
M045	MHL-5000/4	Diazo	63
M045.1			
M048	MHL-3000/2	Diazo	59
M054	MHL-4007	Multi-Spectrum	62
M057	MHL-5007	Multi-Spectrum	64
M057.2	MHL-5007S	Multi-Spectrum	64
M058	MHL-3007	Multi-Spectrum	60
M058.2	MHL-3007S	Multi-Spectrum	60
M059	MHL-1007	Multi-Spectrum	56
M059.2	MHL-1007S	Multi-Spectrum	56
M060	MHL-5020	Diazo	65
M060.2	MHL-5020S	Diazo	65
M061	MHL-4007	Multi-Spectrum	62
M063	MHL-2000/2	Photopolymer	58
M063.1			
M064	MHL-5000/5	Photopolymer	64
M064.1			
M067	MHL-5027	Multi-Spectrum	65
M069			
M069.2	MHL-5027S	Multi-Spectrum	66
M091	MHL-15	Diazo	50
M097.2	MHL-2117S	Multi-Spectrum	59
M105	MHL-17	Diazo	50
M111	MHL-13	Diazo	49
M111.17			
M114	MHL-12	Diazo	49
M122.7	MHL-15	Diazo	50
M124.17	MHL-13	Diazo	49
M125.17	MHL-17	Diazo	50
M223	MHL-4001	Diazo	62
M812	MHL-5007	Multi-Spectrum	64
MP1200T5 5/155	MHL-1200/2	Diazo	57
MP1200T5 5/6J	MHL-1200/1	Diazo	57
MP2000T8/4J	MHL-2000/3	Diazo	58
MP2000T8/4R	MHL-2000/4	Diazo	58
MP3000T8/6J	MHL-3000/2	Diazo	59
MP3000T8/6R	MHL-3000/3	Diazo	59
	MHL-3003	Diazo	60
MP5000T8/V	MHL-5000/4	Diazo	63

# CROSS REFERENCE

## BY MANUFACTURER / LAMP #

勝特力材料 886-3-5753170  
 勝特力电子(上海) 86-21-54151736  
 勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)

MANUFACTURER LAMP #	USHIO LAMP #	APPLICATION PROCESS	PAGE #
<b>TEANECK</b>			
L1250	MHL-170L	Multi-Spectrum	52
<b>THEIMER</b>			
TH 1000 (820190)	MHL-1000	Diazo	55
TH 1007 (820197)	MHL-1007	Multi-Spectrum	56
TH 2000 (820200)	MHL-2000/3	Diazo	58
TH 2008 (820208)	MHL-2000/2	Photopolymer	58
TH 2010	MHL-3000/2	Diazo	59
TH 2030	MHL-15	Diazo	50
TH 2120	MHL-13	Diazo	49
TH 3000 (820390)	MHL-3001	Diazo	59
TH 3007 (820397)	MHL-3007	Multi-Spectrum	60
TH 3020 (822390)	MHL-3020S	Diazo	61
TH 3027 (821397)	MHL-3027S	Multi-Spectrum	61
TH 4000	MHL-4001	Diazo	62
TH 4007	MHL-4007	Multi-Spectrum	62
TH 4010	MHL-4010	Diazo	62
	MHL-17	Diazo	50
TH 500	MHL-12	Diazo	49
TH 500S			
TH 5000 (820596)	MHL-5000	Diazo	63
TH 5007 (820597)	MHL-5007	Multi-Spectrum	64
TH 5010 (821500)	MHL-5000/4	Diazo	63
TH 5017 (821507)	MHL-5000/7	Multi-Spectrum	64
TH 5018 (821508)	MHL-5000/5	Photopolymer	64
TH 5020 (822590)	MHL-5020	Diazo	65
TH 5027 (822597)	MHL-5027	Multi-Spectrum	65
TH 5060	MHL-5020	Diazo	65
TH 5067	MHL-5027	Multi-Spectrum	65
TH 508	MHL-12	Diazo	49
TH 5080	MHL-30	Diazo	50
TH 5090	MHL-17	Diazo	50
TH 510	MHL-12	Diazo	49
TH 6027	MHL-6027S	Multi-Spectrum	66
THS 1000 (820190)	MHL-1000S	Diazo	55
THS 1007 (820197)	MHL-1007S	Multi-Spectrum	56
THS 1507 (823197)	MHL-1507S	Multi-Spectrum	57
THS 2117 (822297)	MHL-2117S	Multi-Spectrum	59
THS 3000 (820390)	MHL-3001S	Diazo	60
THS 3007 (820397)	MHL-3007S	Multi-Spectrum	60
THS 3020 (822390)	MHL-3020S	Diazo	61

MANUFACTURER LAMP #	USHIO LAMP #	APPLICATION PROCESS	PAGE #
<b>THEIMER</b>			
THS 3027 (821397)	MHL-3027S	Multi-Spectrum	61
THS 500	MHL-12	Diazo	49
THS 5000 (820596)	MHL-5000S	Diazo	63
THS 5007 (820597)	MHL-5007S	Multi-Spectrum	64
THS 5020 (822590)	MHL-5020S	Diazo	65
THS 5027 (822597)	MHL-5027S	Multi-Spectrum	66
THS 6027	MHL-6027S	Multi-Spectrum	66
THS 8027 (821897)	MHL-8027S	Multi-Spectrum	67
KX 10 (823110)	UPX-45		68
KX 105	UPX-56		69
KX 110	UPX-50		69
KX 150 (820811)	UPX-80		69
KX 22	UPX-46		68
KX 30 (821310)	UPX-47		69
KX 8	UPX-42		68
<b>THORN</b>			
91-7466	MHL-1000	Diazo	55
	MHL-1007	Multi-Spectrum	56
91-7483	MHL-2000/3	Diazo	58
91-7484	MHL-15	Diazo	50
<b>TOBIAS</b>			
MP3000T8/6J	MHL-3000/3	Diazo	59
<b>OTHER</b>			
PAGA 1000/1	MHL-1000/1	Photopolymer	56
PAGA 1200/1	MHL-1200/1	Diazo	57
PAGA 2000/1	MHL-2000/1	Diazo	58
PAGA 2000/2	MHL-2000/2	Photopolymer	58
PAGA 2000/3	MHL-2000/3	Diazo	58
PAGA 2000/4	MHL-2000/4	Diazo	58
PAGA 3000/2	MHL-3000/2	Diazo	59
PAGA 3000/3	MHL-3000/3	Diazo	59
PAGA 4000/U1	MHL-4000/U1	Multi-Spectrum	61
PAGA 4000/U2	MHL-4000/U2	Photopolymer	61
PAGA 5000/2	MHL-5000/2	Multi-Spectrum	63
PAGA 5000/4	MHL-5000/4	Diazo	63
PAGA 5000/5	MHL-5000/5	Photopolymer	64
PAGA 5000/7	MHL-5000/7	Multi-Spectrum	64

# Double Ended - R7s-12

## SPECIFICATIONS


LAMP DESCRIPTION  
ORDERING CODE

## CROSS REFERENCE

MANUFACTURER - LAMP #  
EQUIPMENT MODEL #

**EHM J120V-300W**  
**1000291**

Watts 300W  
Volts 120V  
Color Temp 3000K  
Approx Lumens 5900Lm  
Average Life 2000Hrs  
Filament C-8  
Bulb Finish Clear  
Base R7s-12




MOL 119.6mm  
Lighted Length (A) 60mm  
Bulb Diameter (B) 9.4mm

KENRO - 532-0018  
V186 K-Lites  
VISUAL GRAPHICS

**EHZ J120V-300WF**  
**1000296**

Watts 300W  
Volts 120V  
Color Temp 3000K  
Approx Lumens 5770Lm  
Average Life 2000Hrs  
Filament C-8  
Bulb Finish Frosted  
Base R7s-12




MOL 119.6mm  
Lighted Length (A) 60mm  
Bulb Diameter (B) 9.4mm

KENRO - 532-0020  
186 Superbeam

**J230V-300W**  
**1000756**

Watts 300W  
Volts 230V  
Color Temp 2900K  
Approx Lumens 4800Lm  
Average Life 2000Hrs  
Filament CC-8  
Bulb Finish Clear  
Base R7s-12




MOL 119.6mm  
Lighted Length (A) 67mm  
Bulb Diameter (B) 9.4mm

MI-TRAK

**J240V-300W**  
**1000774**

Watts 300W  
Volts 240V  
Color Temp 2900K  
Approx Lumens 5000Lm  
Average Life 2000Hrs  
Filament CC-8  
Bulb Finish Clear  
Base R7s-12




MOL 119.6mm  
Lighted Length (A) 67mm  
Bulb Diameter (B) 9.4mm

ILFORD

**J115V-500WE**  
**1000694**

Watts 500W  
Volts 115V  
Color Temp 3050K  
Approx Lumens 10500Lm  
Average Life 1500Hrs  
Filament C-8  
Bulb Finish Clear  
Base R7s-12



MOL 119.6mm  
Lighted Length (A) 65mm  
Bulb Diameter (B) 12mm

勝特力材料 886-3-5753170  
勝特力电子(上海) 86-21-54151736  
勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)

# Double Ended - R7s-12

## SPECIFICATIONS


LAMP DESCRIPTION  
ORDERING CODE

## CROSS REFERENCE

MANUFACTURER - LAMP #  
EQUIPMENT MODEL #

### FCL J120V-500W 1000488

Watts 500W  
Volts 120V  
Color Temp 3000K  
Approx Lumens 11000Lm  
Average Life 2000Hrs  
Filament C-8  
Bulb Finish Clear  
Base R7s-12




MOL 119.6mm  
Lighted Length (A) 57mm  
Bulb Diameter (B) 12mm

AGFA GEVAERT- MK3  
ESKOFOT  
ILFORD  
KENRO - 02-6314  
V18; V24; V184; V185; V240; V242; V243;  
187; 187DM; 241; 241DM;  
MITSUBISHI  
CP-310 Platemaker  
VISUAL GRAPHICS

### J120V-500W/6 1000712

Watts 500W  
Volts 120V  
Color Temp 3000K  
Approx Lumens 11000Lm  
Average Life 2000Hrs  
Filament C-8  
Bulb Finish Clear  
Base R7s-12




MOL 119.6mm  
Lighted Length (A) 67mm  
Bulb Diameter (B) 12mm

SCREEN USA (DS AMERICA)

### FCZ J120V-500WF 1000497

Watts 500W  
Volts 120V  
Color Temp 3000K  
Approx Lumens 10700Lm  
Average Life 2000Hrs  
Filament C-8  
Bulb Finish Frosted  
Base R7s-12




MOL 119.6mm  
Lighted Length (A) 57mm  
Bulb Diameter (B) 12mm

KENRO - 532-0019  
187K; 241; 243  
4800 Superbeam

### FDJ JP120V-500WC6 1000500

Watts 500W  
Volts 120V  
Color Temp 3200K  
Approx Lumens 13250Lm  
Average Life 400Hrs  
Filament C-8  
Bulb Finish Clear  
Base R7s-12




MOL 119.6mm  
Lighted Length (A) 75mm  
Bulb Diameter (B) 12mm

勝特力材料 886-3-5753170  
勝特力电子(上海) 86-21-54151736  
勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)

### FDN JP120V-500WCF6 1000502

Watts 500W  
Volts 120V  
Color Temp 3200K  
Approx Lumens 12800Lm  
Average Life 400Hrs  
Filament C-8  
Bulb Finish Frosted  
Base R7s-12



MOL 119.6mm  
Lighted Length (A) 75mm  
Bulb Diameter (B) 12mm

# Double Ended - R7s-12

## SPECIFICATIONS


LAMP DESCRIPTION  
ORDERING CODE

## CROSS REFERENCE

MANUFACTURER - LAMP #  
EQUIPMENT MODEL #

### JP120V-500WC7 1001079

Watts 500W  
Volts 120V  
Color Temp 3200K  
Approx Lumens 13200Lm  
Average Life 25Hrs  
Filament C-8  
Bulb Finish Clear  
Base R7s-12




MOL 119.6mm  
Lighted Length (A) 62mm  
Bulb Diameter (B) 8mm

ITEK - 190682-001  
175; 185; 275; 400; 560; 613; 615E; 1117;  
1218; 1518; 11800  
KENRO - 02-6314  
187; 240; 241

### JP125V-500WS 1001080

Watts 500W  
Volts 125V  
Color Temp 3400K  
Approx Lumens 16250Lm  
Average Life 25Hrs  
Filament C-8  
Bulb Finish Clear  
Base R7s-12




MOL 127.1mm  
Lighted Length (A) 70mm  
Bulb Diameter (B) 10mm

AB DICK  
157 Exposure  
MULTIGRAPHICS  
835 Exposure  
NUCOGRAPHICS  
1218 Exposure

### DVS J130V-500WB 1000224

Watts 500W  
Volts 130V  
Color Temp 3000K  
Approx Lumens 10500Lm  
Average Life 2000Hrs  
Filament C-8  
Bulb Finish Clear  
Base R7s-12




MOL 119.6mm  
Lighted Length (A) 57mm  
Bulb Diameter (B) 12mm

KODAK  
IM800

### JP220V-500WC 1001084

Watts 500W  
Volts 220V  
Color Temp 3200K  
Approx Lumens 12500Lm  
Average Life 200Hrs  
Filament C-8  
Bulb Finish Clear  
Base R7s-12




MOL 119.6mm  
Lighted Length (A) 62mm  
Bulb Diameter (B) 12mm

勝特力材料 886-3-5753170  
胜特力电子(上海) 86-21-54151736  
胜特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)

### J220V-500WE 1000736

Watts 500W  
Volts 220V  
Color Temp 3000K  
Approx Lumens 9500Lm  
Average Life 2000Hrs  
Filament C-8  
Bulb Finish Clear  
Base R7s-12



MOL 119.6mm  
Lighted Length (A) 65mm  
Bulb Diameter (B) 12mm

AB DICK  
148  
ESKOFOT  
KLIMSCH  
KODAK  
LOGETRONICS  
MI-TRAK  
ROBERTSON  
VISUAL GRAPHICS  
44-00410-203

# Double Ended - R7s-12

## SPECIFICATIONS


LAMP DESCRIPTION  
ORDERING CODE

## CROSS REFERENCE

MANUFACTURER - LAMP #  
EQUIPMENT MODEL #

### JP240V-500WC 1001093

Watts 500W  
Volts 240V  
Color Temp 3200K  
Approx Lumens 12500Lm  
Average Life 200Hrs  
Filament C-8  
Bulb Finish Clear  
Base R7s-12




MOL 117.6mm  
Lighted Length (A) 62mm  
Bulb Diameter (B) 12mm

ILFORD

### JP240V-500WC1 1001858

Watts 500W  
Volts 240V  
Color Temp 3300K  
Approx Lumens 14750Lm  
Average Life 20Hrs  
Filament C-8  
Bulb Finish Clear  
Base R7s-12




MOL 117.6mm  
Lighted Length (A) 60mm  
Bulb Diameter (B) 12mm

ITEK - 190682-003  
175; 275

### J120V-525W 1000716

Watts 525W  
Volts 120V  
Color Temp 3150K  
Approx Lumens 12000Lm  
Average Life 30000Cycles  
20sec. on/30 sec. off  
Filament C-8  
Bulb Finish Clear  
Base R7s-12




MOL 119.6mm  
Lighted Length (A) 65mm  
Bulb Diameter (B) 12mm

AGFA GEVAERT  
RPS2024SA  
HELIOPRINT

### JP225V-525W/HE 1001088

Watts 525W  
Volts 225V  
Color Temp 3150K  
Approx Lumens 13125Lm  
Average Life 30000Cycles  
20sec. on/30 sec. off  
Filament C-8  
Bulb Finish Clear  
Base R7s-12




MOL 117.6mm  
Lighted Length (A) 65mm  
Bulb Diameter (B) 9mm

AGFA GEVAERT  
RPS2024SA  
HELIOPRINT

勝特力材料 886-3-5753170  
勝特力电子(上海) 86-21-54151736  
勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)

### JP245V-525W 1001098

Watts 525W  
Volts 245V  
Color Temp 3150K  
Approx Lumens 13125Lm  
Average Life 30000Cycles  
20sec. on/30 sec. off  
Filament C-8  
Bulb Finish Clear  
Base R7s-12



MOL 119.6mm  
Lighted Length (A) 65mm  
Bulb Diameter (B) 9mm

AGFA GEVAERT  
RPS2024SA  
HELIOPRINT

# Double Ended - R7s-12

## SPECIFICATIONS


LAMP DESCRIPTION  
ORDERING CODE

## CROSS REFERENCE

MANUFACTURER - LAMP #  
EQUIPMENT MODEL #

**J110V-550WB**  
**1000693**

Watts 550W  
Volts 110V  
Color Temp 3050K  
Approx Lumens 13200Lm  
Average Life 1000Hrs  
Filament C-8  
Bulb Finish Clear  
Base R7s-12




MOL 119.6mm  
Lighted Length (A) 60mm  
Bulb Diameter (B) 12mm

AGFA GEVAERT - 12548  
RPS1200; RPS1300; RPS1600;  
RPS1218 Mini

Substitution  
BLV - 12010101

**12010101 (BLV)**  
**1001589**

Watts 550W  
Volts 110V  
Color Temp 3050K  
Approx Lumens 13500Lm  
Average Life 1000Hrs  
Filament C-8  
Bulb Finish Clear  
Base R7s-12




MOL 119.6mm  
Lighted Length (A) 60mm  
Bulb Diameter (B) 12mm

AGFA GEVAERT - 12548  
RPS1200; RPS1300; RPS1600;  
RPS1218 Mini

**JP225V-550WC**  
**1001089**

Watts 550W  
Volts 225V  
Color Temp 3200K  
Approx Lumens 11000Lm  
Average Life 50000Cycles  
20sec. on/30 sec. off  
Filament C-8  
Bulb Finish Clear  
Base R7s




MOL 119.6mm  
Lighted Length (A) 57mm  
Bulb Diameter (B) 12mm

AGFA GEVAERT - 12521  
1230 Camera

Substitution  
BLV - 12170101

**12170101 (BLV)**  
**1001590**

Watts 550W  
Volts 225V  
Color Temp 3200K  
Approx Lumens 11000Lm  
Average Life 50000Cycles  
20sec. on/30 sec. off  
Filament C-8  
Bulb Finish Clear  
Base R7s




MOL 119.6mm  
Lighted Length (A) 57mm  
Bulb Diameter (B) 12mm

AGFA GEVAERT - 12521  
1230 Camera;  
RPS2100; RPS2200; RPS3000

勝特力材料 886-3-5753170  
勝特力电子(上海) 86-21-54151736  
勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)

**JP225V-625WCL**  
**1001090**

Watts 625W  
Volts 225V  
Color Temp 3200K  
Approx Lumens 15500Lm  
Average Life 200Hrs  
Filament C-8  
Bulb Finish Clear  
Base R7s-12



MOL 191.1mm  
Lighted Length (A) 135mm  
Bulb Diameter (B) 12mm

CHADWICK-HELMUTH  
OPTICOPY



# Double Ended - R7s-12

## SPECIFICATIONS


LAMP DESCRIPTION  
ORDERING CODE

## CROSS REFERENCE

MANUFACTURER - LAMP #  
EQUIPMENT MODEL #

### EIG JP120V-750WC 1000299

Watts 750W  
Volts 120V  
Color Temp 3200K  
Approx Lumens 20600Lm  
Average Life 400Hrs  
Filament C-8  
Bulb Finish Clear  
Base R7s-12




MOL 119.6mm  
Lighted Length (A) 62mm  
Bulb Diameter (B) 12mm

VISUAL GRAPHICS  
62-12201-002

### J220V-750WB1 1000738

Watts 750W  
Volts 220V  
Color Temp 3050K  
Approx Lumens 16100Lm  
Average Life 1500Hrs  
Filament C-8  
Bulb Finish Clear  
Base R7s-12




MOL 119.6mm  
Lighted Length (A) 69mm  
Bulb Diameter (B) 12mm

MITSUBISHI  
CP-550 Platemaker  
SCREEN USA (DS AMERICA)

### JP125V-800W 1001081

Watts 800W  
Volts 125V  
Color Temp 3400K  
Approx Lumens 26000Lm  
Average Life 25Hrs  
Filament C-8  
Bulb Finish Clear  
Base R7s-12




MOL 127.1mm  
Lighted Length (A) 72mm  
Bulb Diameter (B) 10mm

AB DICK  
145 Exposure  
155 Exposure  
MULTIGRAPHICS  
875 Exposure  
885 Exposure  
NUCOGRAPHICS  
215 Exposure  
375 Exposure

### JP220V-800WC1 1001085

Watts 800W  
Volts 220V  
Color Temp 3200K  
Approx Lumens 21600Lm  
Average Life 200Hrs  
Filament C-8  
Bulb Finish Clear  
Base R7s-12




MOL 116.6mm  
Lighted Length (A) 70mm  
Bulb Diameter (B) 10mm

AGFA GEVAERT  
11F20-21

勝特力材料 886-3-5753170  
勝特力电子(上海) 86-21-54151736  
勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)

### EME JP240V-800WC1 1000328

Watts 800W  
Volts 240V  
Color Temp 3200K  
Approx Lumens 22000Lm  
Average Life 250Hrs  
Filament C-8  
Bulb Finish Clear  
Base R7s-12



MOL 119.6mm  
Lighted Length (A) 70mm  
Bulb Diameter (B) 12mm

AGFA GEVAERT  
RPS2024SA  
ALAN GRAPHICS  
SCREEN USA (DS AMERICA)  
Camera

# Double Ended - R7s-12

## SPECIFICATIONS


LAMP DESCRIPTION  
ORDERING CODE

## CROSS REFERENCE

MANUFACTURER - LAMP #  
EQUIPMENT MODEL #

### EMF JP240V-800WCF 1000329

Watts 800W  
Volts 240V  
Color Temp 3200K  
Approx Lumens 21400Lm  
Average Life 250Hrs  
Filament C-8  
Bulb Finish Frosted  
Base R7s-12




MOL 119.6mm  
Lighted Length (A) 70mm  
Bulb Diameter (B) 12mm

VISUAL GRAPHICS  
62-12201-001

### FCM JP120V-1000WCF1 1000489

Watts 1000W  
Volts 120V  
Color Temp 3200K  
Approx Lumens 28000Lm  
Average Life 400Hrs  
Filament C-8  
Bulb Finish Clear  
Base R7s-12





MOL 119.6mm  
Lighted Length (A) 65mm  
Bulb Diameter (B) 12mm

ACTI PRODUCTS  
Super V Camera  
RECOGNITION SYSTEMS  
VISUAL GRAPHICS  
40-00463-001

### FHM JP120V-1000WCF1 1000533

Watts 1000W  
Volts 120V  
Color Temp 3200K  
Approx Lumens 27300Lm  
Average Life 400Hrs  
Filament C-8  
Bulb Finish Frosted  
Base R7s-12




MOL 119.6mm  
Lighted Length (A) 65mm  
Bulb Diameter (B) 12mm

勝特力材料 886-3-5753170  
勝特力电子(上海) 86-21-54151736  
勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)

### EJD JP185V-1000WS 1000298


Watts 1000W  
Volts 185V  
Color Temp 3350K  
Approx Lumens 33600Lm  
Average Life 100Hrs  
Filament C-8  
Bulb Finish Clear  
Base R7s-12



MOL 119.6mm  
Lighted Length (A) 70mm  
Bulb Diameter (B) 12mm

### J225V-1000WB (J220/230V-1000WB) 1000739

Watts 1000W  
Volts 225V  
Color Temp 3050K  
Approx Lumens 21500Lm  
Average Life 2000Hrs  
Filament C-8  
Bulb Finish Clear  
Base R7s-12



MOL 191.1mm  
Lighted Length (A) 135mm  
Bulb Diameter (B) 12mm

MI-TRAK


# Double Ended - R7s-12

## SPECIFICATIONS

LAMP DESCRIPTION  
ORDERING CODE

**EKM JP225V-1000WCL**  
**1000310**

Watts 1000W  
Volts 225V  
Color Temp 3200K  
Approx Lumens 25000Lm  
Average Life 200Hrs  
Filament C-8  
Bulb Finish Clear  
Base R7s-12



MOL 191.1mm  
Lighted Length (A) 140mm  
Bulb Diameter (B) 12mm


## CROSS REFERENCE

MANUFACTURER - LAMP #  
EQUIPMENT MODEL #

CHADWICK-HELMUTH  
OPTICOPIY

**J240V-1000WB4**  
**1000760**

Watts 1000W  
Volts 240V  
Color Temp 3050K  
Approx Lumens 22000Lm  
Average Life 1500Hrs  
Filament C-8  
Bulb Finish Clear  
Base R7s-12




MOL 119.6mm  
Lighted Length (A) 66mm  
Bulb Diameter (B) 12mm

SCREEN USA (DS AMERICA)

**JP225V-1500WCL**  
**1001864**

Watts 1500W  
Volts 225V  
Color Temp 3200K  
Approx Lumens 39000Lm  
Average Life 200Hrs  
Filament C-8  
Bulb Finish Clear  
Base R7s-12



MOL 191.1mm  
Lighted Length (A) 137mm  
Bulb Diameter (B) 12mm

CHADWICK-HELMUTH  
OPTICOPIY

勝特力材料 886-3-5753170  
勝特力电子(上海) 86-21-54151736  
勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)

# Double Ended - R7s-15

## SPECIFICATIONS

LAMP DESCRIPTION  
ORDERING CODE

**FDB JP120V-1500WC**  
**1000499**

Watts 1500W  
Volts 120V  
Color Temp 3200K  
Approx Lumens 41200Lm  
Average Life 400Hrs  
Filament C-8  
Bulb Finish Clear  
Base R7s-15



MOL 167.4mm  
Lighted Length (A) 70mm  
Bulb Diameter (B) 13mm

## CROSS REFERENCE

MANUFACTURER - LAMP #  
EQUIPMENT MODEL #

ACTI PRODUCTS  
Super V Camera  
RECOGNITION SYSTEMS

# Double Ended - R7s-18

## SPECIFICATIONS


LAMP DESCRIPTION  
ORDERING CODE

## CROSS REFERENCE

MANUFACTURER - LAMP #  
EQUIPMENT MODEL #

### EHP JPD120V-300WG 1000292

Watts 300W  
Volts 120V  
Color Temp 2900K  
Approx Lumens 5650Lm  
Average Life 2000Hrs  
Filament CC-8  
Bulb Finish Clear  
Base R7s-18




MOL 80.3mm  
Lighted Length (A) 18mm  
Bulb Diameter (B) 12mm

NUARC - VE-598  
SST1418; SST1418-1-3; SST1418-3

### FDA JPD120V-400W 1000498

Watts 400W  
Volts 120V  
Color Temp 3200K  
Approx Lumens 10400Lm  
Average Life 200Hrs  
Filament CC-8  
Bulb Finish Clear  
Base R7s-18




MOL 80.3mm  
Lighted Length (A) 18mm  
Bulb Diameter (B) 15mm

ARGYLE  
VISUAL GRAPHICS  
62-12206-002

### EHR JPD120V-400WG 1000293

Watts 400W  
Volts 120V  
Color Temp 2900K  
Approx Lumens 7750Lm  
Average Life 2000Hrs  
Filament CC-8  
Bulb Finish Clear  
Base R7s-18




MOL 80.3mm  
Lighted Length (A) 20mm  
Bulb Diameter (B) 15mm

KENRO  
2700; 3700; 4150  
7000; 7100; 7350;  
7400  
STAR/GOODKIN

勝特力材料 886-3-5753170  
勝特力电子(上海) 86-21-54151736  
勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)

### FFM JPD120V-420WC1 1000518

Watts 420W  
Volts 120V  
Color Temp 3200K  
Approx Lumens 11000Lm  
Average Life 75Hrs  
Filament CC-8  
Bulb Finish Clear  
Base R7s-18




MOL 80.3mm  
Lighted Length (A) 13mm  
Bulb Diameter (B) 15mm

NUARC - VE-479  
SST1418-1-4;  
VIC1418; VIC1418-15;  
VV1418; VV1418BL; VV1418BL-2; VV1418SS;  
VV1418SSBL; VV1418SSBL-2; VV1418SS-2;  
VV1418-2; VVE1418  
1418SC2-4

### FCB JPD120V-600WD 1000486

Watts 600W  
Volts 120V  
Color Temp 3250K  
Approx Lumens 17000Lm  
Average Life 75Hrs  
Filament CC-8  
Bulb Finish Clear  
Base R7s-18



MOL 95.25mm  
Lighted Length (A) 17mm  
Bulb Diameter (B) 15mm

BROWN - 2-14009-000  
2000; 3000; 4000  
OLEC - L6C2  
AL1KT  
AL1KT-C6  
AL16P  
AL6CX

# Double Ended - R7s-18

## SPECIFICATIONS


LAMP DESCRIPTION  
ORDERING CODE

## CROSS REFERENCE

MANUFACTURER - LAMP #  
EQUIPMENT MODEL #

### FAD JPD120V-650WC 1000471

Watts 650W  
Volts 120V  
Color Temp 3200K  
Approx Lumens 16500Lm  
Average Life 100Hrs  
Filament CC-8  
Bulb Finish Clear  
Base R7s-18




MOL 80.3mm  
Lighted Length (A) 16mm  
Bulb Diameter (B) 15mm

KENRO 2750  
NUARC - VE-366  
NUQ2600; NUQ5300; SST1418-1-6; SST1418-6; VIC1418-15-6; VIC1418-2; VIC1418-25; VIC1418-6; VV1418BL-6; VV1418SS-6; VV1418SSBL-6; VV1418-6  
1418SC2; 2024V-6  
STAR/GOODKIN

### DWY JPD120V-650WS 1000229

Watts 650W  
Volts 120V  
Color Temp 3400K  
Approx Lumens 20000Lm  
Average Life 25Hrs  
Filament CC-8  
Bulb Finish Clear  
Base R7s-18




MOL 80.3mm  
Lighted Length (A) 16mm  
Bulb Diameter (B) 15mm

BROWN - BN8046P  
Spectramatic

勝特力材料 886-3-5753170  
勝特力电子(上海) 86-21-54151736  
勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)

### FCA JPD120V-650WSF 1000485

Watts 650W  
Volts 120V  
Color Temp 3400K  
Approx Lumens 19000Lm  
Average Life 35Hrs  
Filament CC-8  
Bulb Finish Frosted  
Base R7s-18




MOL 80.3mm  
Lighted Length (A) 16mm  
Bulb Diameter (B) 15mm

VISUAL GRAPHICS

### DXK/220V JPD220V-800WC1 1000238

Watts 800W  
Volts 220V  
Color Temp 3200K  
Approx Lumens 20500Lm  
Average Life 75Hrs  
Filament CC-8  
Bulb Finish Clear  
Base R7s-18




MOL 80.3mm  
Lighted Length (A) 25mm  
Bulb Diameter (B) 15mm

NUARC - VE-377  
NUQ3200; NUQ3200A; NUQ4800; NUQ6400A;  
SST1418; SST1418S;  
SST2024; SST2024C; SST2024CS; SST2024S;  
SST2024SB; SST2024SBS; SST3131;  
SST3131S; SSTE2024SB; SSTE2024SBS;  
VV2024M; VV2024MBL; VV2024M2;  
VV2024M2BL; VVE1418-2; VVE2024M;  
VVE2024M2;  
1418SC2-2; 2024V; 2024VBL

### DXK/240V JPD240V-800WC 1000240

Watts 800W  
Volts 240V  
Color Temp 3200K  
Approx Lumens 20500Lm  
Average Life 75Hrs  
Filament CC-8  
Bulb Finish Clear  
Base R7s-18



MOL 80.3mm  
Lighted Length (A) 25mm  
Bulb Diameter (B) 15mm

NUARC - VE-377  
NUQ3200; NUQ3200A; NUQ4800; NUQ6400A;  
SST1418; SST1418S;  
SST2024; SST2024C; SST2024CS; SST2024S;  
SST2024SB; SST2024SBS; SST3131;  
SST3131S; SSTE2024SB; SSTE2024SBS;  
VV2024M; VV2024MBL; VV2024M2;  
VV2024M2BL; VVE1418-2; VVE2024M;  
VVE2024M2;  
1418SC2-2; 2024V; 2024VBL

# Double Ended - R7s-18

## SPECIFICATIONS


LAMP DESCRIPTION  
ORDERING CODE

## CROSS REFERENCE

MANUFACTURER - LAMP #  
EQUIPMENT MODEL #

**BRH JPD120V-1000WC1**  
**1000068**

Watts 1000W  
Volts 120V  
Color Temp 3350K  
Approx Lumens 30000Lm  
Average Life 75Hrs  
Filament CC-8  
Bulb Finish Clear  
Base R7s-18




MOL 95.25mm  
Lighted Length (A) 25mm  
Bulb Diameter (B) 18mm

OLEC - L1K3  
AL1KT

**DKW JPD120V-1000WC5**  
**1000236**


Watts 1000W  
Volts 120V  
Color Temp 3200K  
Approx Lumens 28000Lm  
Average Life 150Hrs  
Filament CC-8  
Bulb Finish Clear  
Base R7s-18



MOL 95.25mm  
Lighted Length (A) 23mm  
Bulb Diameter (B) 18mm

**FBY JPD120V-1000WC5F**  
**1000483**

Watts 1000W  
Volts 120V  
Color Temp 3200K  
Approx Lumens 26000Lm  
Average Life 150Hrs  
Filament CC-8  
Bulb Finish Frosted  
Base R7s-18




MOL 95.25mm  
Lighted Length (A) 23mm  
Bulb Diameter (B) 18mm

OLEC  
AL1KT-K2

**DKN JPD120V-1000WS1**  
**1000234**

Watts 1000W  
Volts 120V  
Color Temp 3400K  
Approx Lumens 33000Lm  
Average Life 50Hrs  
Filament CC-8  
Bulb Finish Clear  
Base R7s-18



MOL 95.25mm  
Lighted Length (A) 23mm  
Bulb Diameter (B) 18mm

BROWN - 2-91702-000  
26, 26SP  
2000; 3000; 4000  
OLEC  
AL1KT-K4

勝特力材料 886-3-5753170  
勝特力电子(上海) 86-21-54151736  
勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)

# Single Ended - G5.3

## SPECIFICATIONS


LAMP DESCRIPTION  
ORDERING CODE

## CROSS REFERENCE

MANUFACTURER - LAMP #  
EQUIPMENT MODEL #

### EYH/FKT JCD120V-250WB 1000453

Watts 250W  
Volts 120V  
Color Temp 3050K  
Approx Lumens 6050Lm  
Average Life 150Hrs  
Filament CC-6  
Burn Position BD/Hor  
Base G5.3





MOL (A) 63.5mm  
Lighted Length (B) 36.5mm  
Bulb Diameter (C) 22mm

NUARC - VE-980

### FBG/FBD JCD120V-500WCP 1000476

Watts 500W  
Volts 120V  
Color Temp 3200K  
Approx Lumens 13200Lm  
Average Life 50Hrs  
Filament CC-6  
Burn Position BD/Hor  
Base G5.3




MOL (A) 76mm  
Lighted Length (B) 44.5mm  
Bulb Diameter (C) 22mm

ITEK - 192511-001  
435 (bottom)

### DYH JCD120V-600WCP 1000246

Watts 600W  
Volts 120V  
Color Temp 3200K  
Approx Lumens 17000Lm  
Average Life 75Hrs  
Filament CC-6  
Burn Position BD/Hor  
Base G5.3





MOL (A) 63.5mm  
Lighted Length (B) 36.5mm  
Bulb Diameter (C) 22mm

ITEK - 192531-001  
430 (top)  
SMITH VICTOR  
SV-403-004  
SV-591; SV-592

### DVY JCD120V-650WSP 1000225

Watts 650W  
Volts 120V  
Color Temp 3400K  
Approx Lumens 20000Lm  
Average Life 25Hrs  
Filament CC-6  
Burn Position BD/Hor  
Base G5.3




MOL (A) 63.5mm  
Lighted Length (B) 36.5mm  
Bulb Diameter (C) 22mm

ITEK - 198005-001  
560  
VISUAL GRAPHICS  
62-12205-005

勝特力材料 886-3-5753170  
勝特力电子(上海) 86-21-54151736  
勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)

### DYJ JCD230V-650WSP 1000247

Watts 650W  
Volts 230V  
Color Temp 3400K  
Approx Lumens 20000Lm  
Average Life 20Hrs  
Filament 2CC-8  
Burn Position BD/Hor  
Base G5.3



MOL (A) 63.5mm  
Lighted Length (B) 42.9mm  
Bulb Diameter (C) 24mm