Honeywell



Representative photograph, actual product appearance may vary.

Due to regional agency approval requirements, some products may not be available in your area. Please contact your regional Honeywell office regarding your product of choice.

VC5E50

VC Series, 50 Ohms, 5.0 W, Fixed, Wirewound Resistor

Features

- Rugged vitreous enamel
- · All-welded construction
- Low cost
- Uniformly tinned leads
- Meets or exceeds MIL-R-26 standards

Typical Applications

- Circuit boards
- Terminal boards
- Automated circuit board population
- Point-to-point wiring
- Load adjustors for power amplifiers

Description

The VC Series resistors are low cost, high quality, axial-lead resistors. The resistors have a ceramic core with a conformal vitreous enamel coating. Each resistor is clearly marked with resistance value and tolerance. Its small size makes it excellent for circuit board, point-to-point or terminal applications. The VC series is made in accordance to MIL-R-26 standards and is ideal for today's technology.

Note: Not suitable for high frequency applications.

勝 特 力 材 料 886-3-5753170 胜特力电子(上海) 86-21-54151736 胜特力电子(深圳) 86-755-83298787 Http://www.100y.com.tw



VC5E50

NW 100X.C TW Pro	oduct Specifications
esistor Type	Fixed
ower Rating	5 W
esistance Value	50 Ohms
erminal Type	Axial
ousing Material	Vitreous enamel
olerance	± 5%
emperature Coefficient	± 150 ppm/ ° C
vailability	Global
NSPSC Code	32121608
NSPSC Commodity	32121608 Wire Wound Resistor
eries Name	VC Series

WWW.100Y.COM.

WWW.100Y.COM.1.W

100Y.COM.TW

勝 特 力 材 料 886-3-5753170 胜特力电子(上海) 86-21-54151736 胜特力电子(深圳) 86-755-83298787 Http://www.100y.com.tw

WWW.100


WWW.100Y.COM

NAOOY.COM.TW

Honeywell

VC5E50

VC Series, 50 Ohms, 5.0 W, Fixed, Wirewound Resistor



WWW.100Y.COM. I W

100Y.COM.TW

B *	A *	Lead GA
5.588 mm [.220 in]	12.7 mm [.500 in]	20
7.010 mm [.276 in]	25.4 mm [1.000 in]	20
10.008 mm [.394 in]	46.838 mm [1.844 in]	20
	5.588 mm [.220 in] 7.010 mm [.276 in]	5.588 mm [.220 in] 12.7 mm [.500 in] 7.010 mm [.276 in] 25.4 mm [1.000 in]

WWW.100Y.COM

WWW.100Y.COM.

勝 特 力 材 料 886-3-5753170 胜特力电子(上海) 86-21-54151736 胜特力电子(深圳) 86-755-83298787

.100Y.COM.TW

WWW.100

Http://www. 100y. com. tw WWW.100Y.COM.TW

^{*} Maximum dimensions WWW.100Y.COM.TW



VC5E50

VC Series, 50 Ohms, 5.0 W, Fixed, Wirewound Resistor

▲ WARNING

PERSONAL INJURY

DO NOT USE these products as safety or emergency stop devices, or in any other application where failure of the product could result in personal injury.

Failure to comply with these instructions could result in death or serious injury.

A WARNING

MISUSE OF DOCUMENTATION

- The information presented in this product sheet (or catalog) is for reference only. DO NOT USE this document as product installation information.
- Complete installation, operation and maintenance information is provided in the instructions supplied with each product.

Failure to comply with these instructions could result in death or serious injury.

WWW.100Y.CON

© Copyright Honeywell Inc. 1998-2004 All rights reserved.

WWW.100Y.COM.T 勝 特 力 材 料 886-3-5753170 胜特力电子(上海) 86-21-54151736 胜特力电子(深圳) 86-755-83298787 Http://www. 100y. com. tw

WWW.100Y.COM.TW