



勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-54151736
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

**CSP/SGP 5.2 x 20mm, 125V/250V, Fast Acting, Glass Tube Fuses with Pigtail,
UL/CSA/PSE-Approved**



Key Specifications/Special Features:

- RoHS compliance
- **Rating/voltage:**
 - **CSP**
 - 100mA to 5A/125V, 250V
 - 5.1A to 7A/125V
 - **SGP**
 - 100mA to 8A/125V, 250V
 - 8.1A to 10A/125V
- **Electrical characteristics:**
 - Load opening time:
 - 135%, 1 hour maximum
 - 200%, 120 seconds maximum
- **Breaking capacity:**
 - 10,000A: 125VAC
 - 35A: 250VAC (1A or less)
 - 100A: 250VAC (1.1A to 3.5A)
 - 200A: 250VAC (3.6A to 10A)
- **Temperature characteristics:**
 - Temperature does not exceed 75 degrees Celsius at 100% rating
- **Structure:**
 - Wire: alloy
 - Cap: brass with nickel plated
 - Body: glass tube
 - Lead: tinned copper wire

Primary Competitive Advantages:

- UL/CSA/PSE