

3 inch bits/sleeves

Wire Gauge AWG	RegMod	Bit Part No.	Sleeve Part No.	Maximum Insulation Diameter Inches	Minimum Terminal Diagonal Inches	Maximum Terminal Diagonal Inches	Terminal Hole Depth Inches	Effective Radius Inches	Terminal Hole Diameter Inches
18	●	KB18	P194		.060	.073	1.000	.150	.075
20	●	WB20M	P194LN	.059	.042	.073	1.000	.150	.075
20-22	●	KB2075	P2224		.042	.073	1.000	.123	.075
22	●	KB22	P2224		.054	.073	.750	.117	.075
22	●	WB2275M	P2224	.052	.049	.074	1.000	.132	.075
22-24	●	KB224LH	P2224		.061	.085	1.000	.117	.086
22-24	●	KB224-1	P2224		.054	.073	1.000	.111	.075
22-24	●	KB224	P2224		.054	.073	.807	.111	.075
22-24	●	WB224M	P2224	.050	.049	.074	1.250	.121	.075
24	●	WB24DH	P2224	.046	.054	.073	1.750	.117	.075
24	●	KB24	P2224		.055	.074	.750	.100	.075
24	●	*WB24SM	P3032LN	.044	.024	.043	.750	.098	.044
24-26	●	WB2426M	P2224	.046	.054	.073	.750	.118	.075
24-26	●	OK2426	P2426		.058	.073	.750	.100	.075
26	●	KB26	P2426		.058	.073	1.000	.100	.075
26	●	*WB26SM	P26LN	.031	.023	.038	.750	.075	.040
26	●	WB26M	P2224	.046	.054	.073	1.000	.118	.075
26	●	*WB2644M	P3032LN	.046	.024	.043	.750	.098	.044
26	●	WB2669M	P2426	.041	.053	.068	1.000	.109	.069
28	●	WB2870M	P2426	.034	.053	.068	1.000	.103	.070
28	●	*WB28SHM	P3032	.030	.031	.035	.750	.066	.036
30	●	*SB30MSH-B	P3032	.027	.031	.035	.750	.064	.036
30	●	*SB30MMK	P3032	.023	.031	.035	.750	.064	.036
30-32	●	*WB3032M	P3032	.027	.034	.038	.750	.064	.040
30-32	●	KB3032	P3032		.034	.038	.750	.064	.040

勝特力材料 886-3-5753170  
 勝特力电子(上海) 86-21-54151736  
 勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)