



BI-COLOR LED DETAIL
(RED, RED/YELLOW, GREEN/ORANGE LED'S ARE ALSO AVAILABLE)

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-54151736
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

SUGGESTED PCB LAYOUT (COMPONENT SIDE)

1. MATERIALS:

HOUSING: HIGH TEMP. THERMOPLASTIC, BLACK, UL 94V-0
CONTACTS: 0.014 INCHES (0.35 MILLIMETERS) THICK PHOSPHOR BRONZE PLATED WITH 150 MICROINCHES (3.81 MICROMETERS) MINIMUM THICK TIN LEAD IN SOLDER AREA. 15 MICROINCHES (0.38 MICROMETERS) MINIMUM GOLD IN LOCALIZED PLATE AREA. ENTIRE CONTACTS PLATED WITH 50 MICROINCHES (1.27 MICROMETERS) MINIMUM THICK NICKEL.
SHIELDED: 0.0098 INCHES (0.25 MILLIMETERS) THICK COPPER ZINC ALLOY PLATED WITH 30 MICROINCHES (0.762 MICROMETERS) MINIMUM THICK NICKEL

2. JACK CAVITY CONFORMS TO FCC RULES AND REGULATIONS PART 68, SUBPART F

3. PART NUMBER: XRJ-S-01-8-8-X-F2

REFER TO LED OPTIONS TABLE FOR ORDERING CODES

NOTES:

UNLESS OTHERWISE SPECIFIED

UNSPECIFIED TOLERANCE: .XX ± 0.010 [0.25]
.X ± 0.006 [0.15]

PCB LAYOUT
TOLERANCE
.XX ± 0.05 [0.002]

CONNECTING THE INFORMATION			
THIS DRAWING IS A CONTROLLED DOCUMENT.			
TITLE	DRG NO.	REV	DATE
RJ45, Connectors, W/LED, BP, 8C, Shielded, Thru-Hole	POWER1 (0712)		
PART NO.	DRG	REV	DATE
XRJM-S-01-8-8-X-F2	VIQ		
	C. TSAI		
			07/12/01