

**YF-3700A Digital Multimeter** is designed and built according to the EMC Directive standards EN 0081-1, EN 50082-1, EN 55011, IEC 801-2/-3 and comply with BSEN 61010-1 / IEC 1010-1. Probe Kit comply with IEC1010-2-31.

勝特力材料 886-3-5753170  
勝特力电子(上海) 86-21-54151736  
勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)

#### ◇DISPLAY

- 3 3/4 digits LCD with maximum reading of 3999
- High Speed Bargraph
- Polarity Indication: Automatic polarity, “-“ display for negative input
- Overload Indication : “4”or “-4” flash with continuous buzz
- Low Battery Indication: Replace battery as LCD display “BATT”

#### ◇FUNCTIONS

- Auto Power Off (30 minutes)
- Function keys: Data Hold, REL, MEM, READ, MIN/MAX, RESET, PWR ON, RANGE
- Test Ranges: ACV, DCV, ACA, DCA, Resistance, Frequency, Diode, Capacitance, Continuity

#### ◇SAMPLING SPEED

- Sampling Rate:
  - 2 times per second for digital display
  - 1 time per second for Capacitance test
  - 20 times per second for Bargraph.

#### ◇ACCESSORIES

- Instruction manual
- Carrying case
- Test leads
- 1.5V Battery x 2 pcs

#### ◇POWER SUPPLY

- Battery type: 1.5V “AA” or UM-3 x 2 pcs
- Battery life : 100 hours approx

#### ◇OPERATION CONDITION

- Operating Temperature & Humidity: 5℃ ~ 40℃,below 80%RH.
- Storage Temperature & Humidity: -10℃ ~ 60℃, below 70%RH.

#### ◇DIMENSION

- Size : 186x86x39mm (LxWxH)
- Weight: about 825g. (battery included)

