

CRIMPING TOOLS WITH TERMINALS POSITIONER

Features:

1. You can fix workpieces on a proper position for convenient, quick, precise and safe Terminal-crimping.
2. Position device can be adjusted to fit terminals of various other diameters, lengths, widths, and thicknesses.
3. Replace the fixed position device easily when crimping different terminals.



*PATENTED



A Socket of Position Device
Make a preparation on this position



The foot hole of position device sticks at suitable hole of your tool.



Prepare first a standard sample, which is then place on the terminal pliers in a crimping state. Let the located platform surface make contact with the bottom of the terminal before locking the platform.



Arrange the contact surfaces of two clamping members to each other and then move the contact surfaces in opposite directions until the contact surfaces make contact with both sides of the terminal before locking the two clamping members.



Fit the stopping member over the clamping member such that one end of the stopping member touches the head of the terminal. Lock the stopping member before testing to make sure that the terminal is pressed properly.



The base may be provided with additional grooves, depending on the requirements of the work piece.

YS-03B For Open Barrel Terminals 0.75mm-4.0mm



YS-03BM For Open Barrel Terminals 0.5mm-2.5mm



YS-03C For Insulated Terminals 1.25mm-5.5mm (1.5mm-6.0mm)



YS-03CO For Cord End Terminals 0.25mm-6.0mm

