

ZTX-3E 型連續變倍體視顯微鏡

ZTX-3E SERIES ZOOM STEREO MICROSCOPE



勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-54151736
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

產品信息

型號：ZTX-3E

規格：1X-4X 物鏡，WF20x 目鏡

技術性能：

1. 視場寬廣，成像清晰，立體感強
2. 45 傾斜雙目觀察，可 360 旋轉，鎖定目鏡，左目鏡同視度調節 $\pm 5\text{dp}$ ，出射筒距調節範圍為 55-75mm
3. 連續變倍物鏡 1X-4X
4. ZTX-3E 系列為三目頭連續變倍顯微鏡
5. 產品通過 CE 認證
6. 輸入電壓為 110V/60Hz 或者 220V/50Hz
7. 每台泡沫包裝，放入內紙箱，二台一個外箱
8. 多種附件可供選擇

選購附件：

1. 目鏡：WF5X，WF10X，WF15，WF20X
2. 附加物鏡 0.5X, 0.75X, 1.5X, 2X
3. 顯微攝像儀
4. 暗視場工作台
5. 珠寶夾
6. 黑白載物板（ 94.5mm ）
7. 磨砂玻璃載物板（ 94.5mm ）
8. 螢光燈 5W

9. 鹵素燈泡 12V10W

10. 環形燈 8W , 10W

11. 木箱

光源配置：

S1. 透射及反射照明均用鹵素燈 12V 10W

S2. 透射及反射照明均用鹵素燈 12V 10W , 可上下調光

S3. 透射照明用螢光燈 5W , 反射照明用鹵素 12V 10W

S4. 透射照明用螢光燈 5W , 反射照明用鹵素 12V 10W , 可調節亮度

光學參數：

目鏡	標準物鏡			附加物鏡							
	物鏡 倍率	視場 範圍	工作 距離	0.5X		0.75X		1.5X		2.0X	
				視場 範圍	工作 距離	視場 範圍	工作 距離	視場 範圍	工作 距離	視場 範圍	工作 距離
5X	1-4X	20-5	85	40-11	172	25-6.5	95	13-3.5	42	10-2.5	28
10X	1-4X	23-5.5	85	52-12	172	30-7	95	15-4	42	11-5.3	28
15X	1-4X	15.5-4	85	36-8.5	172	21.5	95	10.5-2.5	42	8-2	28
20X	1-4X	10.5-3	85	25-5.8	172	14-3.5	95	7-1.8	42	5.5-1.5	28

Product Information

Type: ZTX-3E

Specs: 1-4X Objective, WF20X EYEPIECES

Technical Performance:

1. Sharp stereo erect image over a wide field view
2. 45° inclined and 360° rotational binocular head with locked-ineyepiece. The left ocular-tube with diopter adjustment ± 5 dp, The interpupillary distance is between 55-75mm.
3. Zoom objective 1x-4x
4. ZTX-E series supplied with pillar style stand, ZTX-E-W series supplied with arm curved style stand ZTX-3E series trinocular
5. Electric apparatus has CE approval
6. Power supply 110V/60Hz or 200V/50Hz
7. Each set packed in styrofoam and in an inner box. Three sets in one carton
8. A wide range of optional accessories.

Optional accessories:

1. Eyepiece WH5x(22mm), SWF 10x(23mm), WF 15x(13mm), WF20x(10mm)
2. Auxiliary objective 0.5x, 0.75x, 1.5x, 2x
3. Video Attachment ofr Microscope
4. Darkfield stage, 94.5mm
5. White/black workingplate, 94.5mm

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-54151736
勝特力电子(深圳) 86-755-83298787
Http://www.100y.com.tw

6. fluorescent bulb 5W
7. Halogen bulb 12V/10W
8. Ring fluorescent lighting 8W & 10W
9. Wooden cabinet with lock and key

Optical Parameters:

Eyepiece	Standard Objective			Auxiliary Objective							
	Objective	Field of View	Working Distance	0.5X		0.75X		1.5X		2.0X	
				Field of View	Working Distance	Field of View	Working Distance	Field of View	Working Distance	Field of View	Working Distance
5X	1-4X	20-5	85	40-11	172	25-6.5	95	13-3.5	42	10-2.5	28
10X	1-4X	23-5.5	85	52-12	172	30-7	95	15-4	42	11-5.3	28
15X	1-4X	15.5-4	85	36-8.5	172	21.5	95	10.5-2.5	42	8-2	28
20X	1-4X	10.5-3	85	25-5.8	172	14-3.5	95	7-1.8	42	5.5-1.5	28