

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
 Http://www.100y.com.tw

WIRE/CABLE SPECIFICATION (線材規格書)

Standard		UL3239 22AWG 200°C 6KV		
Item (項目)		Unit (單位)	Specification (規格值)	Tolerance (容差)
General Specification (線種規格)		AWG	22	
芯線結構	Conductor 導體	Material (材質)	Tinned Copper	
		Structure (結構)	No.×mm	22 / 0.14
		Stranded Diameter (絞線外徑)	mm	0.75
	Insulation 絕緣	Material (材質)	Silicone Rubber	
		Average Thickness (平均厚度)	mm	0.70
Color (顏色): White、Red、Black、Blue、Brown、Yellow、Green、Yellow/Green				
Overall Outer Diameter (最後完成外徑)		mm	2.2	±0.1
Electric Characters 電氣特性	Rated Temperature (額定溫度)		°C	200
	Rated Voltage (額定電壓)		KV-DC	6
	Resistance of Insulation (水中常溫絕緣阻抗)		MΩ/km	10
	Withstand Voltage Spark (火花試驗)		KV/Sec	8
Marking	E215834 c兄us AWM STYLE 3239 22AWG 6KV-DC 200°C VW-1 CSA TYPE TV-6 SILICONE RUBBER 200°C NIZING			
Certification	AWM 3239 E215834			
Product Application (產品應用)		Structural Configuration (結構圖):		
<p>適用於各種家用電器, 照明燈具, 工業機器, 電熱製品, 原料溶爐等高溫場所之配線</p> <p><u>The wire can be used in various thermal places ranging from household appliances, lighting devices, industrial machines, to high-temperature furance.</u></p>				