

Bulb Base	Nominal Length Order	Watts in.	Code	Description	Case Qty.	Rated Life	Lumens			Color Temp.		Warning and		Additional Information
							Initial	Mean	Foot-candles	K	CRI	Notes	Cautions	

## SPECIAL APPLICATION LAMPS (CONTINUED)

### COLD TEMPERATURE (CONTINUED)

#### INSTANT START

T12 Single Pin (Fa8)	75	96	47350	F96T12/CW-CT	15	12000	5960	5490	4100	60	11,13,17	101	Plastic jacket
----------------------	----	----	-------	--------------	----	-------	------	------	------	----	----------	-----	----------------

#### HIGH OUTPUT (800mA) RECESSED DOUBLE CONTACT

T12 R17d	35	24	48097	F24T12/CW/HO-CT	12	9000	1570	1300	4100	60	11,13,17	101	Plastic jacket
	60	48	48530	F48T12/SP35/HO-AT	12	12000	4120	3710	3500	73	11,13,17	101	Plastic jacket w/v
			47352	F48T12/SPX30/HO-CT	24	12000	4210	3800	3000	82	11,13,17	101	Plastic jacket
			45976	F48T12/CW/HO-AT	12	12000	3710	3220	4100	60	11,13,17	101	Plastic jacket w/v
	75	60	47353	F60T12/CW/HO-CT	12	12000	4990	4340	4100	60	11,13,17	101	Plastic jacket
	85	72	47346	F72T12/SP35/HO-CT	8	12000	6450	5810	3500	73	11,13,17	101	Plastic jacket
46201			F72T12/SP41/HO-CT	8	12000	6450	5810	4100	72	11,13,17	101	Plastic jacket	
48095			F72T12/SPX35/HO-CT	8	12000	6590	5930	3500	82	11,13,17	101	Plastic jacket	
46199			F72T12/CW/HO-AT	8	12000	6150	5350	4100	60	11,13,17	101	Plastic jacket w/v	
	110	96	45979	F96T12/SP35/HO-CT	8	12000	8920	8030	3500	73	11,13,17	101	Plastic jacket
48096			F96T12/SPX35/HO-CT	8	12000	9060	8160	3500	82	11,13,17	101	Plastic jacket	
45912			F96T12/CW/HO-AT	8	12000	8630	7500	4100	60	11,13,17	101	Plastic jacket w/v	
11918			F96T12/CW/HO/CT	15	12000	8900	7740	4100	60	11,13,17	101	Plastic jacket	
11919			F96T12/D/HO/CT	15	12000	7600	6610	6500	75	11,13,17	101	Plastic jacket	

#### T10 VERY HIGH OUTPUT (1500mA) RECESSED DOUBLE CONTACT

T10 R17d	110	48	10742	F48T10/CW	24	9000	6200	4100	60	4	101	
			46196	F48T10/CW/VHO-CT	12	9000	6010	4100	60	13, 17	101	Plastic jacket
	135	60	17135	F60T10/SP30	24	6000	8500	3000	70	4	101	
39157			F60T10/CW	24	6000	7000	4100	60	4	101		
13002			F60T10/CW 6PK	6	6000	7000	4100	60	4	101		
46197			F60T10/CW/VHO-CT	12	6000	6790	4100	60	13, 17	101	Plastic jacket	
	160	72	13776	F72T10/CW 15PK	15	9000	9700	4100	60	4	101	
46198			F72T10/CW/VHO-CT	8	9000	9400	4100	60	13, 17	101	Plastic jacket	

#### T12 VERY HIGH OUTPUT (1500mA) RECESSED DOUBLE CONTACT

T12 R17d	110	48	34206	F48T12/CW/1500/0	24	10000	7000	4100	60	4	101	
			46195	F48T12/CW/VHO-CT	12	10000	6790	4100	60	15, 17	101	Plastic jacket
	170	72	13762	F72T12/CW/1500/0	15	10000	10800	4100	60	4	101	
			46200	F72T12/CW/VHO-CT	8	10000	10470	4100	60	15, 17	101	Plastic jacket
	220	96	13788	F96T12/CW/1500/0	15	10000	14400	4100	60	4	101	
			46202	F96T12/CW/VHO-CT	8	10000	13960	4100	60	15, 17	101	Plastic jacket

#### DIAZO REPROGRAPHIC 1500mA (SUPERBLUE)

##### T12

T12 Medium BiPin (G13)	120	54	40092	F54" T12/SPB	24	2000					± 2	101
	125	59	39683	F59" T12/SPB	24	2000					± 2	101

##### T17

T17 Mogul BiPin (G20)	180	54	26390	F54" T17/SPB	12	2000					± 2	101
-----------------------	-----	----	-------	--------------	----	------	--	--	--	--	-----	-----

#### APPLIANCE

##### T8

T8 Medium BiPin (G13)	18	22	10257	F22" T8/D/4	24	7500	925	790	6500	75		101	Daylight
			17705	F24" T8/CW/4 6PK	24	7500	1225	1040	4100	60		101	
	19	26	10702	F26" T8/CW/4	24	7500	1275	1085	4100	60		101	
38199			F26" T8/CW/4 6PK	24	7500	1275	1085	4100	60		101		
17704			F28" T8/CW/4 6PK	24	7500	1350	1145	4100	60		101		
	30	10349	F30" T8/CW/4	24	7500	1375	1170	4100	60		101		