


T型



勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

应用: • 电源滤波器 • 大电流差模 • 共模电感器

型号 TYPE	尺寸Dimensions (mm)			电感因数 (AL (nH/N ²) ±10%)		L (CM)	A (CM ²)	V (CM ³)
	A	B	C	-26	-52			
T30	7.8±0.5	3.84±0.4	3.25±0.5	33.5	30.5	1.84	0.06	0.11
T37	9.53±0.5	5.21±0.4	3.25±0.5	28.5	26.0	2.31	0.064	0.147
T38	9.53±0.5	4.45±0.4	4.83±0.5	49.0	49.0	2.18	0.114	0.248
T44	11.2±0.5	5.82±0.5	4.04±0.5	37.0	35.0	2.68	0.099	0.266
T50	12.7±0.5	7.7±0.5	4.83±0.5	33.0	33.0	3.19	0.112	0.358
T50B	12.7±0.5	7.7±0.5	6.35±0.5	43.5	43.5	3.19	0.148	0.471
T50C	12.7±0.5	7.7±0.5	8.51±0.5	61.0	75.0	3.19	0.2	0.637
T50D	12.7±0.5	7.7±0.5	9.53±0.5	72.0	66.0	3.19	0.223	0.711
T60	15.2±0.5	8.53±0.5	5.94±0.5	50.0	47.0	3.24	0.187	0.699
T60D	15.2±0.5	8.53±0.5	11.9±0.5	97.0	94.0	3.24	0.374	1.4
T68	17.5±0.5	9.4±0.5	4.83±0.5	43.5	40.0	4.23	0.179	0.259
T68A	17.5±0.5	9.4±0.5	6.35±0.5	58.0	54.0	4.23	0.242	1.03
T68D	17.5±0.5	9.4±0.5	9.53±0.5	87.0	80.0	4.23	0.358	1.52
T72	18.3±0.5	7.11±0.5	6.6±0.5	90.0	82.0	4.01	0.349	1.4
T80	20.2±0.5	12.6±0.5	6.35±0.64	46.0	42.0	5.14	0.231	1.19
T80B	20.2±0.5	12.6±0.5	9.53±0.64	71.0	63.0	5.14	0.347	1.73
T80D	20.2±0.5	12.6±0.5	12.7±0.64	92.0	83.0	5.14	0.453	2.23
T90	22.9±0.5	14.0±0.5	9.53±0.64	70.0	64.0	5.78	0.395	2.28
T94	23.9±0.5	14.2±0.5	7.92±0.64	60.0	57.0	5.97	0.362	2.16
T106	26.9±0.5	14.5±0.5	11.1±0.64	93.0	95.0	6.49	0.659	4.28
T106A	26.9±0.5	14.5±0.5	7.92±0.64	67.0	67.0	6.49	0.461	3
T106B	26.9±0.5	14.5±0.5	14.6±0.64	124.0	124.0	6.49	0.858	5.57
T130	33.0±0.5	19.8±0.5	11.1±0.64	81.0	79.0	8.28	0.698	5.78
T130A	33.0±0.5	19.8±0.5	5.72±0.64	41.0		8.28	0.361	2.99
T131	33.0±0.5	16.3±0.5	11.1±0.64	116.0	108.0	7.72	0.885	6.84
T132	33.0±0.5	17.8±0.5	11.1±0.64	103.0	95.0	2.96	0.805	6.41
T150	38.4±0.64	21.5±0.5	11.1±0.64	96.0	89.0	9.38	0.887	8.31
T150A	38.4±0.64	21.5±0.5	8.26±0.64	66.0		9.38	0.657	6.16
T157	39.9±0.64	24.1±0.64	12.5±0.76	100.0	99.0	10.1	1.06	10.7
T175	44.5±0.64	27.2±0.64	16.5±0.76	105.0	105.0	11.2	0.34	15
T184	46.7±0.64	24.1±0.64	18.0±0.76	169.0	159.0	11.2	1.88	21
T200	50.8±0.64	31.8±0.64	14.0±0.76	92.0	92.0	13	1.27	16.4
T200B	50.8±0.64	31.8±0.64	25.4±0.76	160.0	155.0	13	2.32	30
T225	57.2±0.64	35.7±0.64	14.0±0.76	98.0	92.0	14.6	1.42	20.7
T225B	57.2±0.64	35.7±0.64	25.4±0.76	160.0	155.0	14.6	2.59	37.8
T249	63.5±0.76	35.7±0.76	25.4±0.76	203.0	203.0	15.6	3.36	52.3
T250	63.5±0.76	31.8±0.76	25.4±0.76	242.0	242.0	15	3.84	57.4
T300	77.2±0.76	49.0±0.76	12.7±0.76	80.0	80.0	19.8	1.68	33.4
T300D	77.2±0.76	49.0±0.76	25.4±0.76	160.0		19.8	3.38	67