

LPS® PRESOLVE®

ORANGE DEGREASER

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)



FEATURES

- Removes adhesives, grease, wax, tar and dirt
- High performance industrial cleaner which cleans on contact
- Fast acting, deep penetration
- Natural based
- Does not contain chlorinated solvents
- Flash point above 100°F (38°C)
- Non-conductive
- Low residue
- Safe on all metals and most plastics
- Meets or exceeds these specifications: McDonnell Douglas CSD#I, AMS 1525B
- Inverta Spray Valve lets you spray in an upright or inverted position

PACKAGES

Net Fill

- 15 oz. (425 grams) aerosol
- 20 fl.oz (591 ml) trigger spray
- 1 gal. (3.78 liters)
- 5 gal. (18.93 liters)
- 55 gal. (208 liters)

Part No.

- 01420
- 01422
- 01428
- 01405
- 01455

APPLICATIONS

- Air Compressors
- Alternators
- Bearings
- Chains & Cable Connections
- Cranes
- Diesel Engines
- Electric Motors
- Fork Lifts
- Gasoline Engines
- Gears
- Generators
- High Voltage Cables
- Power and Air Tools
- Printing Presses
- Pulleys
- Terminals/Switches



Nonfood Compounds Program Listed
 Category Code: C1 Registration # 129025
 (Aerosol); # 059830 (Bulk)

PROPERTIES

- Flash Point:
104°F (40°C)
- Specific Gravity:
.803 @ 77°F (25°C)
- KB Value:
53
- Ozone Depletion Potential:
None

- Dielectric Strength and Breakdown Voltage (ASTM D-877):
>30,000 volts
- Propellant:
Carbon Dioxide



MATERIAL SAFETY DATA SHEETS AVAILABLE UPON REQUEST OR VISIT OUR WEB SITE : WWW.LPSLABS.COM

LPS Laboratories • An Illinois Tool Works Company

P.O. Box 105052 • 4647 Hugh Howell Road • Tucker, GA 30085-5052 • TEL: (800) 241-8334 or (770) 243-8800 • FAX: (800) 543-1563 or (770) 243-8899

Internet Web Site: www.lpslabs.com

©2009 LPS Laboratories • LPS® is a registered trademark of Illinois Tool Works • Printed in U.S.A. • All Rights Reserved • Form #2064 • Rev. 5/2009