

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

迷你數顯扭力扳手

SH-DMTB 迷你扳手



表面處理：拋光鍍鉻

種類：扭力扳手

加工定制：是

材質：工具鋼

制式：公制/英制

特性：數顯

扭力值設定：有較的保護機械螺絲

Model Number	SH-DMTQ06	SH-DMTQ15	SH-DMTQ25
Accuracy	CW:±3% CCW:±4%		
Maximum operating range	6N-m 4.424ft-lb 53.09in-lb 61.22kg-cm	15N-m 11.07ft-lb 132.8in-lb 153kg-cm	25N-m 18.45ft-lb 221.3in-lb 254.9kg-cm
Setting Range	0.3-6N-m 0.221-4.424ft-lb 2.65-53.09in-lb 3.06-61.22kg-cm	0.75-15N-m 0.554-11.07ft-lb 6.638-132.8in-lb 7.649-153kg-cm	1.25-25N-m 0.923-18.45ft-lb 11.07-221.3in-lb 12.75-255kg-cm
Minimal scale unit	0.001 N-m 0.001 ft-lb 0.01 in-lb 0.01 kg-cm	0.001 N-m 0.001 ft-lb 0.01 in-lb 0.01 kg-cm	0.001 N-m 0.001 ft-lb 0.01 in-lb 0.01 kg-cm
Number of memory parameters	30		
LED	2 LED(1 GREEN + 1 RED)		
Vibration warning	Yes (if torque achieves a setting value of 90 %, the vibration warning will begin)		
Operating modes	Peak hold(K) / Track(F)		
Torque Units	N-m, in-lb, ft-lb, kg-cm		
Battery life (Continuous operation)	110hrs.		
Battery life (Standby mode)	1 year		
Operating temperature	-10℃-60℃		
storage temperature	-20℃-70℃		
Humidity	Up to 90% non-condensing		
Drop test	1m		
Shaking test	10G		
Service life test	10000 cycle		
Environment test	Pass		
Electromagnetic - Compatibility (EMC) test	Pass		

Model Number	Bit socket (inches)	Maximum operating range	Setting Range	Max. torque Load / DIN Standards (N-m)
SH-DMTB06	72T, 1/4"	6 N-m	0.3~6 N-m	70.0/62.0
SH-DMTB15	72T, 1/4"	15 N-m	0.75~15 N-m	70.0/62.0
SH-DMTB25	72T, 1/4"	25 N-m	1.25~25 N-m	70.0/62.0

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)