



特性與優點

- 1M Ω Inputs
- **P6101B**
 - 1X, 15MHz, 300V, CATI
- **P6109B**
 - 10X, 100MHz, 300V, CATII
 - Readout
- **P6111B**
 - 10X, 200MHz, 300V, CATII
 - Readout
- **P6112**
 - 10X, 100MHz, 300V, CATII
- **P6114B**
 - 10X, 400MHz, 300V, CATII
- **P6117**
 - 10X, 200MHz, 300V, CATII
- **P3010**
 - 10X, 100MHz (P3010)
- Moded Passive Voltage Probes
- Single Piece, Molded Rubber Body
- Lightweight Ergonomic Design
- 10 Times Improvement in Durability
- HYBRID/SMT Circuitry on Multi-layer Circuit Board for Improved Performance and Reliability
- New Stronger Replaceable Probe Tip
- Safety Certification
 - UL3111-2-031, CSA1010.2.031, EN61010-2-031, IEC61010-2-031
- 1 Year Unconditional Guarantee
- Miniature Probe Tip Compatible with a Wide Range of Tektronix Accessories and Adapters

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-54151736
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

APPLICATIONS

• Mixture of High, Medium and Low Frequency General

Purpose Relative Measurements

- Engineering and Desing
- Service
- Manufacturing

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-54151736
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

規格

Type	Attenuation	Bandwidth Megahertz (MHz)	Comp. Range PicoFarads (pF)	System Input Resistance (MΩ)	Typical Input C PicoFarads (pF)	Input RMS CAT I CAT II (Volts)	Readout	Scope/Product
P6101B	1X	15	NA	1	100	300 V _{RMS} CAT I		All Scopes
P6109B	10X	100	15 to 35	10	13	400 V _{RMS} CAT I 300 V _{RMS} CAT II	X	2211, 2221, 2224, 2230, 2232, 2235A, 2236A, 2245A, 2246A, 2247A, 2252, TAS455, TAS465, TAS475, TDS310, TDS320, TDS340, TDS 340A
P6111B	10X	200	15 to 35	10	14	400 V _{RMS} CAT I 300 V _{RMS} CAT II	X	TAS485, TDS350, TDS360
P6112	10X	100	15 to 35	10	13.3	400 V _{RMS} CAT I 300 V _{RMS} CAT II		TDS200
P6114B	10X	400	10 to 35	10	14.1	400 V _{RMS} CAT I 300 V _{RMS} CAT II	X	TDS380
P6117	10X	200	15 to 35	10	13.3	400 V _{RMS} CAT I 300 V _{RMS} CAT II		THS700
P3010	10X	100	10 to 15	10	13	400 V _{RMS} CAT I 300 V _{RMS} CAT II	X	TDS3012, TDS3012B, TDS3014, TDS3014B

Passive voltage probes are the most commonly use oscilloscope probe. Other specialty probes expand the range and functionality of an oscilloscope as a measurement system, but a general purpose, passive voltage probe is the working end of the oscilloscope, a tool used every day by engineers and technicians.

Two years of customer research, design innovation and an exhaustive test program resulted in a most remarkable family of oscilloscope probes. This family of passive voltage probes is specifically designed for Tektronix analog and digital portable oscilloscopes. The 1X and 10X switchable probes combine the same high quality electrical performance that customers expect from Tektronix with a new rugged mechanical design.

These probes are encased in a resilient, molded rubber body that is virtually indestructible. They are lighter in weight, more comfortable to hold and more reliable than modular probe styles. The probes' replaceable tips are designed to withstand up to 20 pounds of force. Patented integral strain relief allows complete freedom of movement while providing superior cable flex. Each probe has received UL safety certification and meets MIL-T-28800, Class 3, environment specifications - something portable scope users will appreciate.

The P3010, P6101B, P6109B, P6111B, P6112, P6114B and P6117 probes are designed to complement Tektronix family of portable DSO and ART instruments. The core of each probe's performance is supplied by a Tektronix HYBRID/SMT device.

Tektronix instrumentation experience provides an extra margin of quality and reliability to the molded probes that is not commonly available to probe manufacturers. These molded probes have been designed and tested to support the overall system performance and measurement quality that Tektronix oscilloscopes guarantee.

Through the introduction of the molded probes, Tektronix has set a new standard for passive voltage probe styling, performance and durability.



P6109B/P3010



P6117



Standard Accessories

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-54151736
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

配件資訊

P6101B

1X, 15 MHz Passive Voltage Probe.

Includes: 4 pairs of colored cable markers; retractable hook tip;

6 in. ground lead; 2 replacement probe tips;

BNC to probe tip adapter; adjustment tool;

storage pouch; instruction manual (070-7819-07).

P6109B

10X, 100 MHz Passive Voltage Probe with Readout.

Includes: Same as P6101B except instruction manual (070-7849-06).

P6111B

10X, 200 MHz Passive Voltage Probe.

Includes: Same as P6101B except instruction manual (070-8543-05).

P6112

10X, 100 MHz Passive Voltage Probe.

Includes: 4 pairs of colored cable markers; retractable hook tip;
6 in. ground lead; BNC to probe tip adapter;
adjustment tool; instruction manual (070-9694-00).

P6114B

10X, 400 MHz Passive Voltage Probe.

Includes: Same as P6112 except instruction manual (070-9491-02).

P6117

10X, 200 MHz Passive Voltage Probe.

Includes: Same as P6112 except instruction manual (070-9729-00).

P3010

10X, 100 MHz Passive Voltage Probe.

Includes: Same as P6101B except instruction manual (071-0466-00).